

# ULTRANUVO

## MMA ASPHALT PRIMER KIT



UltraNuvo is a clear primer designed for priming asphalt surfaces before application of MMA and PU-based anti-skid and slip-resistant coatings. It has a very short cure time, reaching full strength by the end of the cure time. This enables it to be used as a primer for new laid surfaces as any bitumen “bleed” is caught within the primer and prevented from migrating to the finishing treatment.

### FEATURES AND BENEFITS

- Solvent-free for a more environmentally-friendly solution
- Clear product, to avoid affecting colour of final surface treatment
- Very fast cure, to enable immediate application of final surface treatment and minimise road closure time
- Supplied in kit form with application tools, for ease of use



Clear



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

CALL FREE: 0808 118 1922

MEONUK.COM



**MEON**  
DELIVERING GREAT SURFACES

## PREPARATION:

### SURFACE PREPARATION:

The application surface should be sound and clean, free from grease, oil, rust, scale, dirt, or any other soiling that might affect adhesion or performance.

Whilst we cannot guarantee results on un-oxidised asphalt or tarmacadam, extensive tests have shown a high success rate on such surfaces.

## MIXING:

### MIXING INSTRUCTIONS:

After thoroughly mixing the base resin, add catalyst and slowly mix until there are no more lumps.

### STIRRING TIME:

At least 2 min.

## APPLICATION:

Pour mixed contents onto roller tray and apply to surface with medium pile roller (supplied in UltraNuvo kits).

## CURING:

### CURING TIME:

Rainproof after:

approx. 25 min. @ 20°C

Can be walked on/recoated:

approx. 45 min. @ 20°C

Pot Life:

approx. 10 min. @ 20°C

## TECHNICAL:

### COVERAGE:

Typically 1.8 - 2m<sup>2</sup> per kg

## AFTERCARE AND MAINTENANCE:

Use **UltraClean X795** to clean any uncured UltraNuvo primer from tools and equipment.

## STORAGE AND PACKAGING:

### STORAGE CONDITIONS:

Storage area should be dry, protected from direct sunlight and extremes of temperature - i.e. between 5°C and 20°C.

### SHELF LIFE:

12 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

### SIZES AVAILABLE:

Supplied in a 2.1kg Kit

## HEALTH AND SAFETY:

Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on **023 9220 0606**

### MEON UK

+44 (0)23 9220 0606

MAIL@MEONUK.COM

MEONUK.COM

### MEON IRELAND

+353 (0)1 840 7647

INFO@MEONIRELAND.COM

MEON.IE



**MEON**  
DELIVERING GREAT SURFACES