

## Spectrum MultiGrip W248



# SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) 453/2010

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** Spectrum MultiGrip W248

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified Uses** Industrial application of paints  
**Uses advised against**

### 1.3. Details of the supplier of the safety data sheet

**Supplier** Meon Ltd.  
Railside  
Northarbour Spur  
Portsmouth  
PO6 3TU  
+44 (0) 23 9220 0606  
mail@meonuk.com

### 1.4. Emergency Telephone Number

**Emergency telephone** +44 (0) 808 118 1922

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification of this product has been carried out in accordance with CLP Regulation (EC) no. 1272/2008

Flammable Liquids, Category 2:	H225 Highly flammable liquid and vapour.
Skin Irritation, Category 2:	H315 Causes skin irritation.
Skin Sensitisation, Category 1:	H317 May cause an allergic skin reaction.
Eye Irritation, Category 2:	H319 Causes serious eye irritation.
Respiratory Sensitisation, Category 1	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Specific Target Organ Toxicity, Single Exposure, Category 3	H336 May cause drowsiness or dizziness.
Carcinogenicity, Category 1B:	H350 May cause cancer.
Reproductive Toxicity, Category:	H360Df May damage the unborn child. Suspected of damaging fertility.
Specific Target Organ Toxicity, Repeated Exposure, Category 2	H373 May cause damage to organs through prolonged
Chronic Aquatic Toxicity,	H411 Toxic to aquatic life with long lasting effects.

## Spectrum MultiGrip W248

### Label Elements

CLP Regulation (EC) no. 1272/2008

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H317 - May cause an allergic skin reaction  
 H319 Causes serious eye irritation.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P260 Do not breathe dust, fume, gas, mist, vapours or spray.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P308+P313 IF exposed or concerned: Get medical advice or attention.  
 P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental information

EUH201 Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

### 2.2. Other hazards

PBT

Not applicable.

\*\*\*vPvB

Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Chemical description

Mixture of resins, solvents, pigments and additives.

#### Hazardous components

Chemical Name	CAS Number	EC Number	REACH	Weight %	Classification [Regulation (EC) No. 1272/2008]
Toluene	203-625-9	108-88-3	01-2119471310-51	10%-25%	H225, H304, H315, H336, H361d, H373
Xylene	215-535-7	1330-20-7	01-2119488216-32	2.5%-10%	H226, H304, H312, H315, H319, H332, H335, H373
Ethylbenzene	202-849-4	100-41-4	01-2119489370-35	<3.8%	H225, H304, H332, H373

## Spectrum MultiGrip W248

1-methoxy-2-propanol	203-539-1	107-98-2	01-2119457435-35	0.1%-1.0%	H226, H336
2-pentanone oxime	484-470-6	623-40-5	01-2119980079-27	1.1%-1.0%	H302, H319, H373, H412
lead sulfochromate	215-693-7 235-759-9	1344-37-2 12656-85-8		0.5%-20.0%	H317, H334, H350, H360Df, H373, H400, H410

For the full text of the Hazard Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

#### 4.1. Description of first aid measures

<b>General notes</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
<b>If inhaled</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**In case of skin contact** Remove contaminated clothing.  
Wash skin thoroughly with soap and water or use recognised skin cleanser.  
Do NOT use solvents or thinners.

**In case of eye contact** Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**If swallowed** If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.  
Keep at rest.  
Do NOT induce vomiting.

**Self-protection of the first aider** None.

#### 4.2. Most important symptoms and effects, both acute and delayed

None.

#### 4.3. Indication of any immediate medical attention and special treatment needed

None.

## Spectrum MultiGrip W248

### SECTION 5: Firefighting measures

Flammable. Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### 5.1 Extinguishing media

##### **Suitable extinguishing media**

Alcohol resistant foam, CO<sub>2</sub>, powders and water spray/mist

##### **Unsuitable extinguishing media**

Water jet.

#### 5.2 Special hazards arising from the substance or mixture

##### **Specific hazards**

Fire will produce dense, black smoke.  
Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

#### 5.2 Advice for firefighters Advice or firefighters

##### **Advice or firefighters**

Cool closed containers exposed to fire with water.  
Do not allow run-off from firefighting to enter drains or watercourses.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area.  
Avoid breathing vapours.  
Refer to protective measures listed in Sections 7 and 8.

#### 6.2 Environmental precautions

Do not allow to enter drains or watercourses.  
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see Section 13).  
Clean preferably with a detergent- avoid use of solvents.

#### 6.4 Reference to other sections

None.

### SECTION 7: Handling and storage

#### 7.1 Precautions on safe handling

##### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

## Spectrum MultiGrip W248

Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

Isolate from sources of heat, sparks and open flame.

No sparking tools should be used.

Avoid skin and eye contact.

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8.

Never use pressure to empty container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage areas and containers**

Store in accordance with the Dangerous Substances and Explosive Atmosphere Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.

#### **Notes on joint storage**

Store away from oxidizing agents, from strongly alkaline and strongly acid materials.

#### **Additional information on storage conditions**

Observe label precautions  
Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat and direct sunlight.  
Keep container tightly closed.  
Keep away from sources of ignition.  
No smoking.  
Prevent unauthorised access.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
The principles contained in the HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances, should be observed when storing this product.

### **7.3 Specific end use(s)**

None.

## Spectrum MultiGrip W248

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Contains no substances with occupational exposure limit values.

Chemical name	Physical state	LTEL – 8hr TWA		STEL – 15min		Notes
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
Toluene		50	191	100	384	Sk
Xylene		50	220	100	441	Sk, BMGV
Ethylbenzene		100	441	125	552	Sk
1-methoxy-2-propanol		100	375	150	560	Sk
lead sulfochromate						(WEL)

LTEL - Long Term Exposure Limit, STEL - Short Term Exposure Limit, TWA - Time-Weighted Average.

ppm - parts per million by volume, mg/m<sup>3</sup> - milligrams per cubic metre.

BMGV - Biological Monitoring Guidance Values are given in Table 2 of EH40/2005 Workplace exposure limits.

Carc - Capable of causing cancer and/or heritable genetic damage.

Sen - Capable of causing occupational asthma.

Sk - Can be absorbed through the skin. Dermal absorption may lead to systemic toxicity.

#### 8.2. Exposure controls

##### General advice

Provide adequate ventilation.

Where reasonably practicable this should be achieved using local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particles and solvent vapour below the OEL, suitable respiratory protection must be worn.

##### Respiratory protection

If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

##### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling, use Polyvinyl Alcohol (PVA) or Viton Rubber (FluorRubber).

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

##### Eye protection

Use safety eyewear designed to protect against splash of liquids.

##### Skin protection

Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

## Spectrum MultiGrip W248

### 8.2.2 Environmental exposure controls

Do not allow to enter drains or watercourses.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance (Physical state)	Viscous liquid
Odour threshold	Aromatic hydrocarbons.
Lower	Not determined
Higher	Not determined
Ph	Not determined
Melting point/freezing point (°C)	>-39.3
Initial boiling point and boiling range (°C)	110-140
Flash point (°C)	4
Evaporation rate	Not determined
Flammability/explosive limits -	
Lower %	Not determined
Higher %	Not determined
Vapour pressure	>0.3 kPa
Vapour density (air=1)	Heavier than air
Relative density (g/ml)	1.41-1.55
Solubility(ies)	Miscible with organic solvents
Partition coefficient	2.65-3.20 log Pow
Auto-ignition temperature (°C)	>480
Decomposition temperature (°C)	Not determined
Viscosity	~2.5 poise
Explosive properties	May form explosive mixtures with air
Oxidising properties	

### 9.2 Other information

None.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

Stable under recommended storage and handling conditions. (See Section 7).

### 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

### 10.5 Incompatible materials

No data available.

## Spectrum MultiGrip W248

### **10.6 Hazardous decomposition products**

Carbon monoxide and dioxide, smoke, oxides of nitrogen.

## **SECTION 11: Toxicological information**

### **11.1. Information on toxicological effects**

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Classification, Labelling and Packaging of Substances and Mixtures Regulation (EC) No. 1272/2008, (CLP) and classified for toxicological hazards accordingly.

See Sections 2 and 3 for details.

#### **11.1.2. Mixture**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhoea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

No data available.

### **12.2. Persistence and degradability**

No data available.

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

No data available.

### **12.6. Other adverse effects**

No data available.



## Spectrum MultiGrip W248

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

The European List of Waste classification of this product, when disposed of as waste, is

Waste Code	Name of Waste (according to Commission Decision 2000/532/EC)
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances.

Do not allow to enter drains or watercourses.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

### SECTION 14: Transport information

#### 14.1. UN number

1263

#### 14.2. UN proper shipping name

Paint

#### 14.3. Transport hazard class(es)

Transport labels

Class 3: Flammable liquids.



## Spectrum MultiGrip W248

### **14.4. Packing group**

II

### **14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant.

### **14.6. Special precautions for user**

ADR Tunnel Restriction Code	(D/E)
IMDG EmS	F-E, S-E
IMDG Stowage Category	B

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage

### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **The information in this Safety Data Sheet is required pursuant to:**

- Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No.1907/2006, (REACH).
- Classification, Labelling and Packaging of substances and mixtures, Regulation (EC) No.1272/2008, (CLP).
- The Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR).
- The Control of Substances Hazardous to Health Regulations, 2002, (COSHH).
- The Health and Safety at Work etc. Act, 1974, (HSWA).

#### **Approved Codes of Practice and Guidance notes relevant to this Safety Data Sheet:**

- The European Chemicals Agency (ECHA) Guidance on the compilation of safety data sheets, Version 2.1.
- CEPE Guideline for Safety Data Sheets, 9th Edition.
- HSE Approved Code of Practice and Guidance, Dangerous Substances and Explosive Atmospheres.
- HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances.
- HSE publication, EH40/2005 Workplace exposure limits.

### **15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

Full text of Hazard Statements referred to in Section 3.

H225: Highly flammable liquid and vapour.  
H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H361d: Suspected of damaging the unborn child.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H412: Harmful to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction.

## Spectrum MultiGrip W248

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350: May cause cancer.

H360Df: May damage the unborn child. Suspected of damaging fertility.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

### *Disclaimer*

*This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.*