

CLEARSEAL X260

SOLVENT BASED ACRYLIC SEALER



ClearSeal X260 is a single pack solvent based acrylic sealer. It is a very fast drying product to allow rapid return to traffic, whilst providing a gloss finish which is durable and long-lasting. It is fully sprayable using airless spray equipment for fast application; it can also be applied by hand. ClearSeal X260 can be used on a wide range of Spectrum lining and coating systems.

FEATURES AND BENEFITS

- Resists soiling
- Leaves an easy clean surface
- Improves visibility, safety and productivity
- Durable and long-lasting
- Fast drying



Clear



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

CALL FREE: 0808 118 1922

MEONUK.COM



MEON
DELIVERING GREAT SURFACES

PREPARATION:

SURFACE PREPARATION:

The application surface should be sound and clean, free from grease, oil, rust, scale, dirt, or any other soiling that might affect adhesion or performance. In any case, but especially in the case of overcoating existing line markings, it is further recommended that test areas be coated to ensure good adhesion and/or compatibility with the substrate/previously applied coatings

MIXING:

MIXING INSTRUCTIONS:

Stir thoroughly before use.

SPRAY APPLICATION:

ClearSeal X260 must be thinned up to 20% by volume using **Meon SF Thinners X290**.

ROLLER OR BRUSH APPLICATION:

ClearSeal X260 is supplied ready to use.

APPLICATION:

APPLICATION TECHNIQUES:

We recommend the use of airless spray equipment. Roller or brushes can be also be used if spray equipment is not available.

Do not apply when: either the air or surface temperature is below 10°C; when there is mist, fog, or snow; when rain is imminent; when humidity is high or when the surface is wet with condensation; either during the application or likely during the drying period.

CURING:

Touch dry:	15 - 30 minutes
Walk on time:	1 hour
Traffic time:	4 hours
Full cure:	4 hours
Recoat:	2 - 4 hours

Technical Data @ 15°C and 65% relative air humidity.

TECHNICAL:

COVERAGE:

Approx. 4m² / kg

COATS REQUIRED:

One is generally sufficient but a second coat can be laid for extra protection.

FILM THICKNESS:

DFT:	150 microns
WFT:	250 microns

AFTERCARE AND MAINTENANCE:

Uncured ClearSeal X260 can be cleaned off equipment and tools using **Meon UltraClean X792**.

Can be cleaned with water or mild detergent. Floor coatings should not be scrubbed, or subjected to steam cleaning or hot water above 60°C.

STORAGE AND PACKAGING:

STORAGE CONDITIONS:

Storage area should be dry, protected from direct sunlight and extremes of temperature - i.e. between 5°C and 20°C.

SHELF LIFE:

6 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

SIZES AVAILABLE:

Supplied in 12kg tins.

HEALTH AND SAFETY:

Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on **023 9220 0606**.

MEON UK

+44 (0)23 9220 0606
MAIL@MEONUK.COM
MEONUK.COM

MEON IRELAND

+353 (0)1 840 7647
INFO@MEONIRELAND.COM
MEON.IE



MEON
DELIVERING GREAT SURFACES