

# FLOORLINE F212

## INTERNAL ACRYLIC LINE MARKING PAINT



Spectrum HYBRID FloorLine F212 is an acrylic line marking paint for internal applications such as warehousing and facilities. It has an increased gloss level from our standard acrylic paints which helps reduce dirt pickup and is easier to clean, whilst maintaining the high quality and ease of use being a spray applied single pack product. FloorLine F212 delivers a high quality line marking in a single pass application without requiring a sealer therefore reducing application time and overall downtime which a typical internal application would incur.

### FEATURES AND BENEFITS

- No Sealer required - reduced downtime
- Increased gloss - reduced dirt pick up and easy to clean
- Spray applied - fast and efficient application



White



Black



Yellow



Traffic Red  
RAL 3020



Traffic Blue  
RAL 5017



Traffic Green  
RAL 6024

CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

CALL FREE: 0808 118 1922

MEONUK.COM



**MEON**  
DELIVERING GREAT SURFACES

## PREPARATION:

The application surface should be sound and clean, free from grease, oil, rust, scale, dirt, or any other soiling that might affect adhesion or performance. In any case, but especially in the case of overcoating existing line markings, it is further recommended that test areas be coated to ensure good adhesion and/or compatibility with the substrate.

Concrete - should be clean, dry and free from dust, dirt, grease and other contaminants etc. Do not apply to newly laid concrete. Surfaces to be coated should be at least 4 weeks old and have a moisture content of less than 7%.

Please note that any smooth/polished surface will require special preparation; please call or email pictures of your specific situation and we will advise on recommended preparation procedure. Test trials should be carried out in the first instance on a small area.

### PRIMERS:

Concrete - use **Meon UniPrime X250**

## MIXING:

Mix thoroughly before use. This product is supplied ready to use and does not usually need thinning. If thinning is required, use **Meon SF Thinners X290**.

## APPLICATION:

FloorLine F212 is applied using airless spray equipment but can also be applied by brush or roller. We recommend using a 215 yellow lining tip for a 50mm line. For best finish, it is recommended the edges are masked off to get a straight edge using **Meon ProGaff Tape** applied using the **Meon StraightLine tape dispenser**.

Do not apply when the air or surface temperature is below 5°C or less than 3°C above dew point; when the surface is wet with condensation or likely to be during the drying period.

## CURING:

TOUCH DRY:	TRAFFIC TIME:	FULL CURE:
15-30 minutes	4 hours	4 hours

Technical data @ 15°C and 65% relative humidity

## TECHNICAL:

### TYPICAL COVERAGE:

m <sup>2</sup> per kg	g/m <sup>2</sup>	50mm line per 20kg kit
2.0	481	800m

**GLOSS LEVEL:** 11.5 GU

### FILM THICKNESS:

<b>WFT:</b>	370µm
<b>DFT:</b>	270µm

## AFTERCARE AND MAINTENANCE:

Use **Meon UltraClean X792** to clean uncured FloorLine F212 from tools and equipment.

## STORAGE:

### STORAGE CONDITIONS:

Storage area should be dry, protected from direct sunlight and extremes of temperature - i.e. between 5°C & 20°C. If product is stored for more than 30 days, full and thorough mechanical mixing will be required before using.

### SHELF LIFE:

6 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

### SIZES AVAILABLE:

Supplied in 20kg tins.

## HEALTH AND SAFETY:

Avoid inhalation of vapours and contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection. Take additional care when spraying under high pressure. Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on **023 9220 0606**.

### MEON UK

+44 (0)23 9220 0606  
 MAIL@MEONUK.COM  
 MEONUK.COM

### MEON IRELAND

+353 (0)1 840 7647  
 INFO@MEONIRELAND.COM  
 MEON.IE



**MEON**  
 DELIVERING GREAT SURFACES