

SURESTRIBE W218

SPRAYABLE WATER BASED PAINT



SureStripe W218 is an environmentally friendly water-based acrylic product for internal line marking which is fast drying. The water-based formulation is odourless which is ideal for applications in any indoor environment, and is also much safer than solvent based alternatives. SureStripe W218 can be applied onto most typical internal surfaces including power-floated concrete and steel, and is fully sprayable which allows for fast application and neat results. SureStripe W218 is packaged in 6kg and 20kg tins, with a range of colours available.

FEATURES AND BENEFITS

- Fully sprayable - fast and neat applications
- Solvent and lead free - low odour
- Available in 6kg and 20kg tins
- Range of colours available



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

CALL FREE: 0808 118 1922

MEONUK.COM



MEON
DELIVERING GREAT SURFACES

PREPARATION:

Previously painted floors - As with all coating applications, suitable pre-treatment of the floor is of the utmost importance. Old paint, especially with suspect adhesion or of an unknown type, should be completely removed. Some paints may still lift, be softened, or cause poor inter-coat adhesion when this system is applied on top of them. So, it is always advisable on any surface to check for suitability and defects by undertaking small-scale trials. If the old paint is satisfactory, clean and abrade the surface in the normal way.

Heavily contaminated floors - SureStripe W218 will not adhere satisfactorily to deposits of grease, oils etc. It will be necessary to mechanically abrade the floor to remove the excess contamination.

New floors/uncoated surfaces - for best results prime with Meon UniPrime W252 before applying SureStripe W218. It is important to allow sufficient drying between the coats.

Concrete - should be clean, dry and free from dust, dirt, grease and other contaminants etc. Do not apply to newly laid concrete. Surfaces to be coated should be at least 4 weeks old and have a moisture content of less than 7%.

Please note that any smooth/polished surface will require special preparation; please call or email pictures of your specific situation and we will advise on recommended preparation procedure. Test trials should be carried out in the first instance on a small area.

PRIMERS:

Recommended to use **Meon UniPrime W252**

MIXING:

Stir thoroughly before use.

Thinning: This product is supplied ready to use and does not need thinning.

APPLICATION:

Best results are obtained in warm (minimum 10°C and rising), dry conditions with a good through draught. SureStripe W218 can be applied using airless spray equipment, we recommend using a 315 tip for 100mm line @ 180 WFT. For best finish, it is recommended the edges are masked off to get a straight edge using **Meon ProGaff Tape** applied using the **Meon StraightLine** tape dispenser and apply SureStripe W218 with mini roller, brush or airless machine. To maximise line clarity and longevity, apply a water-based sealer from the **Meon ClearSeal** range as a final coat.

CURING:

Surface Dry:	15 minutes
Hard Dry:	2 hours
Overcoat/Seal:	2 hours

Technical data @ 15°C and 65% relative humidity. Keep coated areas dry for a minimum of 24 hours following application.

TEMPERATURES:

The drying and curing process will slow down at low temperatures and stop altogether whenever it falls below 10°C.

Do not apply when ambient temperature falls below 10°C or relative humidity exceeds 85%.

CHEMICAL RESISTANCE:

7-10 days should be allowed before being exposed to chemicals, pollutants and mechanical stress.

TECHNICAL:

PRACTICAL COVERAGE:	Approx. 3m ² /kg (60m @ 50mm wide per kg)
VOLUME SOLIDS:	50%
MASS SOLIDS:	60%
FLASH POINT:	N/A
GLOSS LEVEL:	Matt
WFT:	180 microns
Can be measured using a Meon Wet Film Thickness Gauge .	

AFTERCARE AND MAINTENANCE:

Uncured SureStripe W215 can be cleaned off equipment and tools using **Meon UltraClean W990**.

STORAGE AND PACKAGING:

STORAGE CONDITIONS:

Storage area should be dry, protected from direct sunlight and extremes of temperature - i.e. between 5°C & 20°C. If product is stored for more than 30 days, full and thorough mechanical mixing will be required before using.

SHELF LIFE:

12 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

SIZES AVAILABLE:

Supplied in 6kg and 20kg tins.

HEALTH AND SAFETY:

Avoid inhalation of vapours and contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection. Take additional care when spraying under high pressure. Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on **023 9220 0606**.

MEON UK

+44 (0)23 9220 0606
MAIL@MEONUK.COM
MEONUK.COM

MEON IRELAND

+353 (0)1 840 7647
INFO@MEONIRELAND.COM
MEON.IE



MEON
DELIVERING GREAT SURFACES