

Spectrum Vialine F216

Hazard pictograms



Signal word

Danger

Hazard statement(s)

H225 - Highly flammable liquid and vapour

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H362 - May cause harm to breast-fed children

H411 - Toxic to aquatic life with long lasting effects

Precautionary statement(s)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 - Take action to prevent static discharges.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378 - In case of fire: Use ABC powder extinguisher to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information

EUH066 - Repeated exposure may cause skin dryness or cracking.

Substances that contribute to the classification

N-butyl acetate; Ethyl acetate; Acetone; Butanone ; Alkanes, C14-C17, chloro

2.3. Other hazards

Other hazards

Product fails to meet PBT/vPvB criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance

Non-applicable

3.2. Mixtures

Chemical description







Acrylic resin

Components

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH 01-2119485493-29-XXXX	N-butyl acetate⁽¹⁾ Regulation1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	ATP CLP00 10 - <20 %
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH 01-2119475103-46-XXXX	Ethyl acetate⁽¹⁾ Regulation1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	ATP CLP00 2.5 - <15 %
CAS: 67-64-1	Acetone⁽¹⁾		ATP CLP00 2.5 - <10 %

Spectrum Vialine F216

EC: 200-662-2 Index: 606-001-00-8 REACH 01-2119471330-49-XXXX	Regulation1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger		
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH 01-2119457290-43-XXXX	Butanone⁽¹⁾ Regulation1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	ATP CLP00 	2.5 - <10 %
CAS: 85535-85-9 EC: 287-477-0 Index: 602-095-00-X REACH 01-2119519269-33-XXXX	Alkanes, C14-17, chloro⁽¹⁾ Regulation1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362; EUH066 - Warning	ATP ATP01 	2 - <5 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH 01-2119488216-32-XXXX	Xylene⁽²⁾ Regulation1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified 	<1 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH 01-2119489370-35-XXXX	Ethylbenzene⁽²⁾ Regulation1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	ATP ATP06 	<0.25 %
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH 01-2119471310-51-XXXX	Toluene⁽²⁾ Regulation1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	ATP CLP00 	<0.01 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the risk of the substances consult sections 11, 12 and 16.

SECTION 4: First aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

General information

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

Inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

Ingestion/Aspiration

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

Skin contact

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

Spectrum ViaLine F216

Eye contact Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

4.2. Most important symptoms and effects, both acute and delayed

Acute and delayed effects are indicated in sections 2 and 11.

4.3. Indication of any immediate medical attention and special treatment needed

Non-applicable.

SECTION 5: Firefighting measures

Flammable. Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Suitable extinguishing media If possible, use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2. Special hazards arising from the substance or mixture

Specific hazards As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3. Advice for firefighters

Advice or firefighters Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2. Environmental precautions

Environmental precautions Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up It is recommended:

Spectrum ViaLine F216

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4. Reference to other sections

Reference to other sections See sections 8 and 13.

SECTION 7: Handling and storage

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions on safe handling

Precautions for safe manipulation Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

Technical recommendations for the prevention of fires and explosions Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

Technical recommendations to prevent ergonomic and toxicological risks Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

Technical recommendations to prevent environmental risks Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for storage Minimum Temp.: 5 °C
Maximum Temp.: 25 °C
Maximum Time.: 6 months

General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5.

7.3. Specific end use(s)

Specific end use(s) Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Substances whose occupational exposure limits have to be monitored in the work environment.

Identification	Environmental limits		
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	IOELV (8h)	200 ppm	734 mg/m ³
	IOELV (STEL)	400 ppm	1468 mg/m ³
Acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m ³
	IOELV (STEL)		

Spectrum ViaLine F216

Butanone CAS: 78-93-3 EC: 201-159-0	IOELV (8h)	200 ppm	600 mg/m ³
	IOELV (STEL)	300 ppm	900 mg/m ³
Xylene CAS: 330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m ³
	IOELV (STEL)	200 ppm	884 mg/m ³
Toluene CAS: 100-88-3 EC: 203-625-9	IOELV (8h)	50 ppm	192 mg/m ³
	IOELV (STEL)	100 ppm	384 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	47.9 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	6.7 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859.7 mg/m ³	859.7 mg/m ³	102.34 mg/m ³	102.34 mg/m ³
Ethyl acetate	Oral	Non-applicable	Non-applicable	4.5 mg/kg	Non-applicable

Spectrum Vialine F216

CAS: 141-78-6 EC: 205-500-4	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m ³	Non-applicable
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Non-applicable	Non-applicable	0.58 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	28.75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14.8 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	8.13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
	Inhalation	226 mg/m ³	226 mg/m ³	56.5 mg/m ³	56.5 mg/m ³

PNEC:

Identification				
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35.6 mg/L	Fresh water	0.18 mg/L
	Soil	0.0903 mg/kg	Marine water	0.018 mg/L
	Intermittent	0.36 mg/L	Sediment (Fresh water)	0.981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.0981 mg/kg
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650 mg/L	Fresh water	0.24 mg/L
	Soil	0.148 mg/kg	Marine water	0.024 mg/L
	Intermittent	1.65 mg/L	Sediment (Fresh water)	1.15 mg/kg
	Oral	200 g/kg	Sediment (Marine water)	0.115 mg/kg
Acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10.6 mg/L
	Soil	29.5 mg/kg	Marine water	1.06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30.4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3.04 mg/kg
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55.8 mg/L
	Soil	22.5 mg/kg	Marine water	55.8 mg/L
	Intermittent	55.8 mg/L	Sediment (Fresh water)	284.74 mg/kg
	Oral	1000 g/kg	Sediment (Marine water)	284.7 mg/kg
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	STP	80 mg/L	Fresh water	0.001 mg/L
	Soil	11.9 mg/kg	Marine water	0.0002 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	13 mg/kg
	Oral	10 g/kg	Sediment (Marine water)	2.6 mg/kg
Xylene	STP	6.58 mg/L	Fresh water	0.327 mg/L

Spectrum Vialine F216

CAS: 1330-20-7 EC: 215-535-7	Soil	2.31 mg/kg	Marine water	0.327 mg/L
	Intermittent	0.327 mg/L	Sediment (Fresh water)	12.46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12.46 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9.6 mg/L	Fresh water	0.1 mg/L
	Soil	2.68 mg/kg	Marine water	0.01 mg/L
	Intermittent	0.1 mg/L	Sediment (Fresh water)	13.7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1.37 mg/kg
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13.61 mg/L	Fresh water	0.68 mg/L
	Soil	2.89 mg/kg	Marine water	0.68 mg/L
	Intermittent	0.68 mg/L	Sediment (Fresh water)	16.39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16.39 mg/kg



8.2. Exposure controls

General safety and hygiene measures in the work place



As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.



Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.



As the product is a mixture of several substances, the resistance of the glove material cannot be predicted in advance with total reliability and has therefore to be checked prior to the application.

Spectrum Vialine F216

Ocular and facial protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004 /A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

 Mandatory foot Protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.
--	---	---	---	---

Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1 D.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

For complete information see the product datasheet

Appearance

Physical state at 20 °C	Liquid
Appearance	Fluid
Colour	White or Yellow

Spectrum ViaLine F216

Odour	Characteristic
Odour threshold	Non-applicable *
Volatility	
Boiling point at atmospheric pressure	56 to 79 °C
Vapour pressure at 20 °C	11.9 kPa
Vapour pressure at 50 °C	41.91 kPa
Evaporation rate at 20 °C	Non-applicable*
Product description	
Density at 20 °C	1400 to 1500 kg/m ³
Relative density at 20 °C	1.4 to 1.5
Dynamic viscosity at 20 °C	Non-applicable*
Kinematic viscosity at 20 °C	Non-applicable*
Kinematic viscosity at 40 °C	Non-applicable*
Concentration	Non-applicable*
pH	Non-applicable*
Vapour density at 20 °C	Non-applicable*
Partition coefficient n-octanol/water at 20 °C	Non-applicable*
Solubility in water at 20 °C	Non-applicable*
Solubility properties	Non-applicable*
Decomposition temperature	Non-applicable*
Melting point/Freezing point	Non-applicable*
Explosive properties	Non-applicable*
Oxidising properties	Non-applicable*
Flammability	
Flash point	<10 °C
Flammability (solid, gas)	Non-applicable*
Autoignition temperature	421 °C
Lower flammability limit	Not available
Upper flammability limit	Not available
Explosive	
Lower explosive limit	Non-applicable*
Upper explosive limit	Non-applicable*
9.2. Other information	
Surface tension at 20 °C	Non-applicable*
Refraction index	Non-applicable*

* Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2. Chemical stability

Stability Chemically stable under the conditions of storage, handling and use.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

Spectrum Vialine F216

10.4. Conditions to avoid

Applicable for handling and storage at room temperature

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5. Incompatible materials

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6. Hazardous decomposition products

Hazardous decomposition products See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

The experimental information related to the toxicological properties of the product itself is not available.

Dangerous health implications

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

Ingestion (acute effect)

Acute toxicity

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.

Corrosivity/Irritability

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Inhalation (acute effect)

Acute toxicity

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

Corrosivity/Irritability

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

Contact with the skin and the eyes (acute effect)

Contact with the skin

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.

Contact with the eyes

Produces eye damage after contact.

CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

Mutagenicity

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Reproductive toxicity

May cause harm to breast-fed children

Sensitizing effects

Spectrum Vialine F216

Respiratory	Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
Cutaneous	Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
Specific target organ toxicity (STOT) - single exposure	Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
Specific target organ toxicity (STOT) - repeated exposure	
Specific target organ toxicity (STOT)-repeated exposure	Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
Skin	Repeated exposure may cause skin dryness or cracking.
Aspiration hazard	Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
Other information	

Specific toxicology information on the substances

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23.4 mg/L (4 h)	Rat
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23.5 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Non-applicable	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17.2 mg/L (4 h)	Rat
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation	28.1 mg/L (4 h)	Rat

Acute Toxicity Estimate (ATE mix)

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

Spectrum Vialine F216

SECTION 12: Ecological information

The experimental information related to the ecotoxicological properties of the product itself is not available.

12.1. Toxicity

Identification	Acute toxicity		Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	23.5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Toluene CAS: 108-88-3 EC: 203-625-9	LC50	13 mg/L (96 h)	Carassius auratus	Fish
	EC50	11.5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae

12.2. Persistence and degradability

Identification	Degradability		Biodegradability	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BOD5	1.36 g O ₂ /g	Concentration	100 mg/L
	COD	1.69 g O ₂ /g	Period	14 days
	BOD5/COD	0.81	% Biodegradable	83 %
Acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.96	% Biodegradable	96 %
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2.03 g O ₂ /g	Concentration	Non-applicable
	COD	2.31 g O ₂ /g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
Xylene CAS: 1330-20-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days

Spectrum Vialine F216

EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	90 %
	BOD5	2.5 g O ₂ /g	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3. Bioaccumulative potential

Identification	Bioaccumulation potential		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF		4
	Pow Log		1.78
	Potential		Low
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF		30
	Pow Log		0.73
	Potential		Moderate
Acetone CAS: 67-64-1 EC: 200-662-2	BCF		1
	Pow Log		-0.24
	Potential		Low
Butanone CAS: 78-93-3 EC: 201-159-0	BCF		3
	Pow Log		0.29
	Potential		Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF		9
	Pow Log		2.77
	Potential		Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF		1
	Pow Log		3.15
	Potential		Low
Toluene CAS: 108-88-3 EC: 203-625-9	BCF		13
	Pow Log		2.73
	Potential		Low

12.4. Mobility in soil

Identification	Absorption/desorption		Volatility	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2.478E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Koc	59	Henry	13.58 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.324E-2 N/m (25 °C)	Moist soil	Yes
Acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2.93 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.304E-2 N/m (25 °C)	Moist soil	Yes
2-butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5.77 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.396E-2 N/m (25 °C)	Moist soil	Yes

Spectrum Vialine F216

Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524.86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798.44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.859E-2 N/m (25 °C)	Moist soil	Yes
Toluene CAS: 108-88-3 EC: 203-625-9	Koc	178	Henry	672.8 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.793E-2 N/m (25 °C)	Moist soil	Yes

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Product fails to meet PBT/vPvB criteria.

12.6. Other adverse effects

Other adverse effects Not described.

SECTION 13: Disposal considerations

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Code 08 01 11*
Description Waste paint and varnish containing organic solvents or other dangerous substances
Waste class (Regulation (EU) No 1357/2014) Dangerous

Type of waste (Regulation (EU) No 1357/2014) HP14 Ecotoxic, HP3 Flammable, HP4 Irritant - skin irritation and eye damage

Waste management (disposal and evaluation) Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management In accordance with Annex II of Regulation (EC) No. 1907/2006 (REACH) the community or state provisions related to waste management are stated.
 Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014.

SECTION 14: Transport information

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for Air Transport.

14.1. UN number

ADR 2019 and RID 2019 UN1263
IMDG 38-16 UN1263
IATA/ICAO 2019 UN1263

14.2. UN proper shipping name

ADR 2019 and RID 2019 PAINT
IMDG 38-16 PAINT
IATA/ICAO 2019 PAINT

Spectrum ViaLine F216

14.3. Transport hazard class(es)

ADR 2019 and RID 2019	3
IMDG 38-16	3
IATA/ICAO 2019	3
Transport Labels	



14.4. Packing group

ADR 2019 and RID 2019	II
IMDG 38-16	II
IATA/ICAO 2019	II

14.5. Environmental hazards

ADR 2019 and RID 2019	Yes
IMDG 38-16	Yes
IATA/ICAO 2019	Yes

14.6. Special precautions for user

ADR 2019 and RID 2019	
Special regulations	163, 367, 640D, 650
Tunnel restriction code	D/E
Physico-Chemical properties	See Section 9
Limited quantities	5 L
IMDG 38-16	
Special regulations	367, 163
EmS code	F-E, S-E
Physico-Chemical properties	See Section 9
Limited quantities	5 L
Segregation group	Non-applicable
IATA/ICAO 2019	
Physico-Chemical properties	See Section 9

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

ADR 2019 and RID 2019	Non-applicable
IMDG 38-16	Non-applicable
IATA/ICAO 2019	Non-applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH) Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer Non-applicable

Spectrum Vialine F216

Article 95, REGULATION (EU) No 528/2012 Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000
E2		200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- “whoopee” cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

‘For professional users only’.

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors

Contains Acetone. Product under the provisions of Article 9

Specific provisions in terms of protecting people or the environment

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation

The product could be affected by sectorial legislation.

15.2. Chemical safety assessment

Chemical safety assessment

The supplier has not carried out evaluation of chemical safety.

SECTION 16: Other information

Legislation related to safety data sheets

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet

Non-applicable

Spectrum Vialine F216

which concerns the ways of managing risks

Texts of the legislative phrases mentioned in section 2

H336 - May cause drowsiness or dizziness.
H362 - May cause harm to breast-fed children.
H411 - Toxic to aquatic life with long lasting effects.
H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3.

CLP Regulation (EC) no. 1272/2008

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Acute Tox. 4: H332 - Harmful if inhaled
Aquatic Acute 1: H400 - Very toxic to aquatic life
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Lact.: H362 - May cause harm to breast-fed children
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
STOT SE 3: H335 - May cause respiratory irritation
STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure

STOT SE 3: Calculation method
Lact.: Calculation method
Aquatic Chronic 2: Calculation method
Flam. Liq. 2: Calculation method (2.6.4.3)
Eye Irrit. 2: Calculation method

Advice related to training

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol–water partition coefficient
Koc: Partition coefficient of organic carbon

Spectrum ViaLine F216

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.