

# Independent Lab Results & Certifications

## Table of Contents

Summary	2
NSF Standard Testing	3
Other contaminants confirmed for removal	5
Bacteria growth	9
Limescale testing	10
Other certifications	11

## Release Notes

The lab results are for PitcherPro available for sales worldwide from June 2023.

Last updated 2024-01-15

Magnus Jern, R&D Director TAPP Water

# Summary

PitcherPro has been tested and certified to remove more than 80 contaminants from tap water. The Product is designed to be used with public tap water where the water is microbiologically safe and has been adequately disinfected. The tests are defined on this basis.

This document summarizes the certifications and lab tests.

## Water Filtration Certified by



# NSF Standard Testing<sup>1</sup>



The product has been tested according to NSF/ANSI Standard 42 (Aesthetic Effects) and Standard 53 (Health Effects).

Test results confirmed by SGS tested in November 2021, Tap Score test by SimpleLab with water samples from Los Angeles, California November 2021 and Austrian Water Institute in Vienna with water samples from Barcelona, Spain 2021-2024.

## NSF/ANSI 42 - Aesthetic Effects

TAPP Water’s Drinking Water System, PitcherPro has been tested according to NSF/ANSI Standard 42 for the reduction of the following substances. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system.

Contaminant	Percent reduction**	Influent challenge concentration (mg/L unless specified)	Maximum permissible product water concentration (mg/L unless specified)
Chlorine	95%	2.0 +/- 10%	> or =50%
Particulate Class II	> 95%	At least 10,000 particles/mL	> or =85%

The tests have been carried out up to 450 L.

## NSF/ANSI 53 - Health Effects

PitcherPro has been tested according to NSF/ANSI Standard 53 for the reduction of the following substances. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system.

<sup>1</sup> Disclaimer: The use of the NSF logo is only to certify that the product has been tested in accordance with NSF standards. The product has not been certified by NSF.

Contaminant	Percent reduction**	Influent challenge concentration (mg/L unless specified)	Maximum permissible product water concentration (mg/L unless specified)
Alachlor*	>98%	0.050	0.001
Atrazine*	>98%	0.100	0.003
Benzene*	>99%	0.081	0.001
Chlordane	>99%	0.04 +/- 10%	0.002
Chloroform (TTHM)	>99%	0.300	0.015
2, 4-D*	98%	0.110	0.0017
Lead pH 6.5	>95%	0.15 +/- 20%	0.01
Lead pH 8.5	>95%	0.15 +/- 20%	0.01
Lindane	>99%	0.055	0.00001
Mercury pH 6.5	>99%	0.006 +/- 10%	0.002
Mercury pH 8.5	>99%	0.006 +/- 10%	0.002
TRIHALOMETHANES* (TTHM) (Chloroform; Bromoform; Bromodichloromethane; Dibromochloromethane)	>99%	0.300	0.015
Turbidity	>98%	10 +/- 10% NTU	0.5 NTU

Source data:

Before filtration: <https://gosimplelab.com/dd4be3b3fdd5229adf45302256abad81789195d1>

After filtration: <https://gosimplelab.com/a6e5e2ec6c5cc7ae9d1c30faf7cfd8697576f8ff>

## Other contaminants confirmed for filtration/removal

PitcherPro has been tested with the following contaminants at the maximum allowed limit unless otherwise specified.

Contaminant	Percent reduction (from influent challenge)	Influent challenge concentration (mg/L unless specified)	Maximum Allowed Limit concentration (mg/L unless specified)
<b>Pathogens</b>			
Clostridium	90%	100 UFC / 100ml	0
eColi	80-90%	100 NMP / 100ml	0
Enterococcus	90%	100 UFC / 100ml	0
<b>Chemical parameters</b>			
Cyanide total	90%	50 µg +/- 20%	50 µg
Fluoride	70%	1.5 +/- 20%	1.5
Mercury	90%	1 µg +/- 20%	1 µg
Nitrites	50-70%	0.1 +/- 10%	0.1
Nitrates	50-70%	50 +/- 10%	50
<b>Metals</b>			
Aluminium	90%	200 µg	200 µg
Antimony	90%	5 µg	5 µg
Arsenic	50%	10 µg	10 µg
Barium	90%	1000 µg	1000 µg
Cadmium	90%	5 µg	5 µg
Copper	80%	2000 µg	2000 µg
Iron	80%	200 µg	200 µg

Lead	95%	10 µg	10 µg
Manganese	80%	50 µg	50 µg
Nickel	80%	20 µg	20 µg
Selenium	80%	10 µg	10 µg
Sodium	0%	200 µg	200 µg
Zinc	80%	5000 µg	5000 µg
<b>Chlorine bi-products</b>			
1,2 Dichloromethane	>95%	3 µg +/- 10%	3 µg
Total Trichloroethylene and Tetrachloroethylene	>95%	10 µg +/- 10%	10 µg
Trichloroethylene*	>95%	-	-
Tetrachloroethylene*	>95%	-	-
<b>Chlorine bi-products</b>			
Total Trihalomethanes	>95%	100 µg +/- 10%	100 µg
4 individual*	>95%	-	-
<b>HAAs</b>			
Total haloacetic acids	>95%	60 µg +/- 10%	60 µg
<b>Pesticides</b>			
Chlordane	>95%	2 µg +/- 10%	2 µg
Heptachlor	>95%	0.4 µg +/- 10%	0.4 µg
Lindane	>95%	0.2 µg +/- 10%	0.2 µg
Additional 11 confirmed by EPA*	>95%	-	-

<b>Herbicides</b>			
2,4 -D	>95%	70 µg +/-10%	70 µg
Atrazine	>95%	3 µg +/-10%	3 µg
Additional 9 confirmed by EPA*	>95%	-	-
Total Herbicides	>95%	0.5 µg +/-10%	0.5 µg
<b>Pharmaceuticals*</b>			
Atenolol	>95%	-	-
Carbamazepine	>95%	-	-
Estrone	>95%	-	-
Meprobamat	>95%	-	-
Trimethoprim	>95%	-	-
<b>Perfluorinated chemicals (PFAS)*</b>			
PFOA	>95%	-	-
PFOS	>95%	-	-
PFNA	>95%	-	-
Microplastics	>99%	100 pieces / L with each piece larger than 2 µg	<= 1

\* Not tested by TAPP Water due to lack of labs that can perform testing. Reduction in accordance with NIH, EPA and CDC testing of activated carbon block filters with a 1-2 micron rating. See [what activated carbon filters remove and reduce](#).

Research by NIH, EPA and CDC of the activated carbon block filtration used in PitcherPro shows that this filter will also reduce the following contaminants by 95% or more (note that some are duplicates):

<b>Solvent/ Organic contaminant/ Alcohol</b>	<b>VOC</b>	<b>Pesticides &amp; Insecticides</b>	<b>Herbicides</b>	<b>Other (Inorganic compounds)</b>
n-butylphthalate	Bromodichloromethane	Malathion	2,4-D	Calcium Hypochlorite
1,2-Dichlorobenzene	Tetrachloroethylene	Aldrin	Deisopropylatrazine	Ozone
1,3-Dichlorobenzene	Dibromochloromethane	Demeton-O	Linuron	Chlorine dioxide
2-Methylbenzenamine		MCPA	Alachlor	
1,4-Dichlorobenzene		Anthracene	Desethylatrazine	
Methyl naphthalene		Azinphos-ethyl	MPitcherProp	
Biphenyl		Dieldrin	Atrazine	
p-chlorocresol		Carbofuran	Metazachlor	
2-Methylbutane		Parathion	Bentazone	
2,2-Bipyridine		Pentachlorophenol	Monuron	
2,5-Dichlorophenol		Endosulfan	Bromacil	
Bis(2-Ethylhexyl)Phthalate		Endrin	2,4-Dichlorophenoxy	
3,6-Dichlorophenol		Hexachlorobenzene	Diuron	
Naphthalene		Hexachlorobutadiene	Propazine	
Nitrobenzene		Isodrin	Simazine	
m-Nitrophenol		DDT	Terbutryn	
p-Bromophenol			Triclopyr	
Diethyl Phthalate			Cyanazine	
o-Nitrophenol			Isoproturon	
Butylbenzene				



2,4-Dinitroresol				
p-Nitrophenol				
2,4-Dinitrotoluene				
2,6-Dinitrotoluene				
Chlorobenzene				
4-Chloro-2-nitrotoluene				
Ethylbenzene				
2-Chlorophenol				
Chlorotoluene				
Chrysene				
Hexane				
1,3,5-Trimethylbenzene				
m-Cresol				
m-Xylene				
Isooctane				
o-Xylene				
Cyclohexane				
p-Xylene				
2,4-Xylenol				

\* Not tested by TAPP Water due to lack of labs that can perform testing. Reduction in accordance with NIH, EPA and CDC testing of activated carbon block filters with a 1-2 micron rating. See [what activated carbon filters remove and reduce](#).

## Bacteria growth

This is a summary of the tests carried out on PitcherPro Gen 3 by SGS in Shenzhen in September 2022.

Sample	Bacteria count	Comment
New cartridge	<1	
Cartridge after 1 week with daily usage (about 50 liters)	11	Below requirement of 100 cfu /L

Cartridge after 2 weeks with daily usage (about 150 liters)	25	Below requirement of 100 cfu /L
Cartridge after no use for 3 days	110	Above requirement of 100 cfu /L
Cartridge after flushing the unused filter for 30 seconds	45	Below requirement of 100 cfu /L

Based on the testing we will also include the following guidelines for PitcherPro (note that PitcherPro Compact should be changed more frequently).

For optimum performance, it is essential that the filter cartridge be replaced on a regularly scheduled basis as follows:

- (a) every 3 months; \*
- (b) when the unit's rated capacity has been reached (max 3 months);\*\*
- (c) the flow rate diminishes; or
- (d) the filter becomes saturated with bad tastes and odors.\*\*\*

Failure to replace the filters in accordance with the recommendations may result in contaminated poorly tasting water.

\* Time estimates for PitcherPro are based on 3-4 liters per day for an average household.

\*\* 3 month maximum is based build up of contaminants in the filter and bacteria growth

\*\*\* For very hard water or highly chlorinated water the cartridges may need to be replaced more frequently

## Limescale testing

These tests were carried out by TAPP Water on PitcherPro in Barcelona in December 2022.

Sample	Limescale formation	Comment
Input water (week / volume)	Hardness of 324 mg CaCO <sub>3</sub> /l and 0.38 LSI	Very high limescale formation
Filtered water		
0 / 0 L	Reduced by 99%	Not visible
4 / 100 L	Reduced by 87%	Not visible
8 / 200 L	Reduced by 84%	Slightly visible

12 / 300 L	Reduced by 81%	Slightly visible
------------	----------------	------------------

The test indicates a reduction of over 87% up to 100 L and 81% up to 300 L. The reduction of limescale will vary dependent on the hardness of the water and the specific mix of minerals and salts.

Notes:

Tests carried out with water boilers to weigh and see visible change of scale formation over time.

## Other certifications

**US Food Grade FDA and European Legislation on Food Contact Materials** - Product does not apply any danger to health or environment according to article 3 in Framework Regulation 1935/2004/EC. Manufactured according to Regulation 2023/2006/EC on good manufacturing practice.

**European Standard EN 1208:2005 Compliant** - European Standard EN 1208:2005 for chemicals used for treatment of water intended for human consumption.

**RoHS2 Compliant (EU)** - Does not contain prohibited substances above the maximum concentration values (MCV) listed in Article 4 and Annex II of the European Union directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (recast), also known as RoHS2.

**REACH Compliance (EU)** - Ensure the product does not contain any chemicals on the REACH SVHC List

**BPA Free** - Ensure that the product has been verified to not contain any BPA

**Cruelty Free** - The product and services do not harm or kill animals anywhere in the world

**Eco-friendly** - The products and services meeting high environmental standards throughout their life-cycle: from raw material extraction, to production, distribution and disposal.

**Lead free** - The product does not contain any lead



For more information contact us on [support@tappwater.co](mailto:support@tappwater.co)