




C3L



## Please visit: www.mailboxproducts.co.uk

Dimensions L x W x H (mm)	1200 x 1000 x 160		
Weight (kg)	22.0		
Material *3	HDPE, Virgin material		
Load capacity (kg) *2	Static 5000	Dynamic 1250	In racking system 850
		Options	
Characteristics Colour: light grey		Central box retainers	
	9°C, briefly up to +90°C		
Colour: light grey Runners: 3, welded Rims: 7 mm	0°C, briefly up to +90°C	Central box retainers	
Colour: light grey Runners: 3, welded Rims: 7 mm Temperatur stability: -30°C to +40	0°C, briefly up to +90°C Container 20': <b>141</b> Container 40': <b>300</b>	Central box retainers	

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- \*1 All technical data include characterisic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- \*2 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.
  Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
- In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20°C.
- \*3 Although still within ISO compulsory range, the load-bearing test results using pallets made from regranulated material show slightly more variation than those from virgin HDPE.

**T:** +44 (0)161 330 5577

**F:** +44 (0)161 330 5576

E: sales@mailboxproducts.co.uk