

Please visit: www.mailboxproducts.co.uk

Technical data *1			
Dimensions L x W x H (mm)	1200 x 1000 x 160		
Weight (kg)	23.5		
Material *3	HDPE, Regranulated material		
Load capacity (kg) *2	Static 5000	Dynamic 1250	In racking system 1000
Charactaristics		Ontions	

Characteristics

Colour: black/light blue Runners: 5, unwelded Rims: 5 mm

Antislip: Yes, 5 antislip strips

Temperatur stability: -30°C to +40°C, briefly up to +90°C Manufactured from regranulated material of one single type

Options

Transponder

Reinforcement profiles


Rims

Loading quantities (pcs/approx.)

Container	Container 20': 141 Container 40': 300	Container 40' High Cube: 340 Conventional trail er 45' high cube container: 390
Truck	MEGA-Trailer : 468	Jumbo: 540

Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- *1 All technical data include characterisic features, which have been tested under specially defi ned conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
- In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 400 h at a room temperature of approx. 20°C.
- *1 Although still within ISO compulsory range, the load-bearing test results using pallets made from regranulated material show slightly more variation than those from virgin HDPE.