





Component	Stock #	Description
Blank	NEPS86LMF-MHX	MHX Elite Pro 7'2" 6-12lb Light Power Mod-Fast Action
Reel Seat	VSSM16/BD	Fuji VSS Spinning Seat Graphite Body Size 16
Seat Hood	KSKSS16/ASH	Fuji SK2 Graphite Hood for BGKS Foregrip KSKSS
Fore Grip	BGKS16C	Foregrip for Fuji SK2 Hood and Nut KSKSS16
Rear Grip	FGV16RC	Contoured Split Grip for Fuji VSS Spinning Reel Seat
Fighting Butt	CFB-2	Split-Grip Fighting Butt with Tenon
Butt Cap	CBC-2	CRB Composite Butt Caps
Winding Check (2)	RWC-425	Black Rubber Winding Checks
Guides	LZR Spinning	CRB LZR Spinning Guides + LZR Running Guides
Tip Top	GLZT-6-4	CRB LZR Light-Duty Tip Top Guides - Model LZT
Hook Keeper	ARHK-GS	CRB Arrow Drop Shot Hook Keeper

Parts chosen based on builders preferences.

GUIDE CHOICE & SPACING

Guides	Fuji Alconite Guides	Spacing From Tip to Ring
1st	GRZG-6	3"
2nd	GRZG-6	6-1/2"
3rd	GRZG-6	10-1/2"
4th	GRZG-6	15"
5th	GRZG-6	19-3/4"
6th	GRZG-6	24-1/2"
7th	GRZG-6	29"
8th	GRZG-6	34-1/2"
9th	GYRZG-6	40-1/2"
10th	GYRZG-12	47"
11th	GYRZG-25	55"

IN this RECIPE











6.5"

FROM THE BUILDER:

- Guide Spacing is based off Size 2500-3000 Spinning Reel
- Rear Grip is placed 6-1/2" from the bottom of the blank
- Hook Keeper is placed 1/2" from top of Fore Grip when Grip is screwed in closed/locked position
- Winding checks used on rear grip and fighting butt. No Winding check needed on fore grip

TARGET SPECIES:

Bonefish, Redfish, Sea Trout

LURES:

Flats Jig, Jerkbait

ABOUT THE BLANK:



TORAY FIBER

50 million modulus. Toray 12K High Modulus Fiber of 50 million modulus with 640 ksi and a Nano Resin System.



NANO RESIN SYSTEM

Nano resin formula unlocks higher specific modulus, enhanced sensitivity, and increased impact resistance.