

## **Product Name: Matte Wall Sealer**

### **Product Description**

Matte Wall Sealer is a 100% acrylic clear finish that is non-yellowing and provides a protective topcoat with excellent clarity and extremely low sheen. It is water based and resists water, abrasion, household grime, stains and is easy to apply by brush or roller. Provides extra durability to delicate finishes in areas that will receive added traffic or moisture such as bathrooms, kitchens, hallways, etc.

### **Where to Use**

Apply over any interior/exterior previously painted and cured surface, decorative paints and plasters that require protection and interior wood, all where a uniform matte finish is desired. Do not use over oil based finishes.

### **Surface Preparation**

Surface must be sound, dry, free from any dirt, grease, loose particles and contamination that will resist penetration and adhesion.

### **Application**

Gently stir by hand before use. Do not use a drill/paddle and do not “whip” air into Matte Wall Sealer. It is important to stir to a homogenous mixture and incorporate all of the fillers at the bottom of the can before use. When applying over porous plaster, stone or wood, thin with up to 10% with water prior to use. For other painted surfaces use as supplied. Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics etc.).

Apply with quality bristle brushes and rollers that are suitable for water based, clear finishes. Apply in a uniform and thin layer to completely cover surface. Avoid runs, sags and drips by applying multiple thin layers instead of a heavy layer. Recoat time is 1—2 hours depending on temperature and humidity. Repeat applying layers until surface is well sealed. Depending on porosity, this may take several layers.

### **Coverage**

250-300 square feet per Gallon.

### **Dry Time**

Dry to touch in 30 minutes. Recoat time is 1-2 hours depending on temperature and humidity.

### **Clean Up**

Clean tools with warm water and soap. Any splashes on surrounding surfaces should be rinsed off immediately with plenty of water.



## Handling and Storage

Close container after use. Protect from freezing. Store at room temperature. Consult with local authorities for methods of disposal.

## Health and Safety

Use in accordance with safe handling practices. These include: \*Avoid eye and skin contact. \*Wash hands after use. \*When spraying or sanding use a NIOSH approved respirator. \*Provide adequate ventilation.

**KEEP FROM REACH OF CHILDREN.**

**First Aid:** EYE CONTACT: Flush with water for 15 minutes. SEE DOCTOR if any symptoms persist. SKIN CONTACT: Wash with soap and water. SEE DOCTOR if skin irritation occurs. INHALATION: Remove subject to fresh air. SEE DOCTOR if symptoms persist. INGESTION: Seek medical attention.

VOC: <50 g/l