

ANNIE SLOAN

SATIN PAINT

PRODUCT INFORMATION SHEET

PRODUCT DETAILS



WASHABLE & WIPEABLE



QUICK DRYING



EXPERTLY TESTED



WATER BASED

- Suitable for interior wood and metal.

SHEEN LEVEL

- Satin (10% sheen)

VOC LEVELS

- VOC LEVELS <5g/L
- UK/EU - Minimal
- US / CA - Very Low

SAFETY /AIR RATING

- Certified as Toy Safe (EU Toy Safety Directive BS EN 71-3:2019).
- EU Indoor air rating: A+



INTRODUCTION

Annie Sloan Satin Paint has been designed for use indoors. Annie Sloan Satin Paint will give a robust yet beautiful soft-sheen finish on any internal wooden or metallic surface. It has been specially formulated to be easy to apply and contains self-levelling properties to give a modern look. Annie Sloan Satin Paint is child friendly, low VOC, and easy to clean. All 14 colours are matched to our Annie Sloan Wall Paint range.



ONE SIZE AVAILABLE

750ml / 25 US fl oz

If you require a smaller amount of product in order to test for colour, use the corresponding Annie Sloan Wall Paint sample. Although the finish will be different the colours are the same.

COVERAGE

750ml is enough to cover approximately 11 square metres.

- Actual coverage is dependent on surface porosity and application.

PREPARATION

All surfaces must be clean, dry, and free from any dust, debris or oil-based contaminants. We advise using a water-based detergent such as sugar soap to thoroughly clean.

METAL PREPARATION

Thoroughly sand the surface, clean, and degrease any unpainted metal surfaces. Previously painted metal surfaces should be sanded back to ensure the removal of any loose or flaking paint. Specialist primers should be used to ensure longevity of Annie Sloan Satin Paint and to protect the metal underneath.

RADIATORS

Make sure the radiator has been turned off and allowed to cool completely. Allow a minimum of four hours drying time before turning on the radiator.

NEW INTERIOR WOOD

For best results when painting fresh woodwork use a diluted coat of Annie Sloan Satin Paint as a base layer.

PREVIOUSLY PAINTED INTERIOR WOOD

Remove any unsound, peeling or flaking paint. Use a diluted coat of Annie Sloan Satin Paint if making a drastic colour change.

COMPLICATIONS:

WEEPING KNOTS

Apply heat to the area to draw out as much resinous material as possible. Use a palette knife to remove. Clean using white spirit and allow area to dry before painting.

FILLED REPAIRS IN WOOD

Allow filler to dry, sand back if necessary, and ensure all dust has been removed before starting to paint.

PAINTING OVER PREVIOUSLY PAINTED GLOSS PAINT, WAXED OR LACQUERED SURFACES

Thoroughly sand, clean and degrease any surfaces previously painted with gloss paint, wax or lacquer before using Annie Sloan Satin Paint.



ANNIE SLOAN

SATIN PAINT

PRODUCT INFORMATION SHEET

APPLICATION

Always stir thoroughly before use.

RECOMMENDED APPLICATION BY BRUSH

Apply a reasonably thick coat of Annie Sloan Satin Paint using a high quality fine tipped synthetic bristled brush (eg Annie Sloan Flat Brushes). Apply the paint in one direction (i.e vertically) and then the other (i.e horizontally) using a cross-hatch technique to achieve the desired coverage. Avoid overworking the paint, as this will cause the paint to degrade. Full coverage should be achieved after 2 coats, although a third may be necessary if making a dramatic colour change.

APPLICATION BY ROLLER

Annie Sloan Satin Paint can be applied using the Annie Sloan foam rollers to achieve a good finish with minimal stippling or "orange peel" appearance. Rollers will coat the surface with a thinner layer of paint than a brush would, therefore additional coats may be required to achieve full coverage.

DRYING TIME AND REAPPLICATION



- Touch dry in 1 hour, though this is dependent on environmental factors and the thickness with which the paint has been applied. Recoat once touch dry.
- Recommended 2 -3 coats (3 if an extreme colour change is needed).
- Allow up to 14 days to "cure" and reach optimum hardness and durability.
- Allow extra drying time when using Annie Sloan Satin Paint in bathrooms. Surfactant leaching can occur when newly painted surfaces are exposed to humidity or steam before the paint has had a chance to fully dry.

CLEAN UP

For best results, clean brushes or rollers by removing as much paint as possible before ending use. Then clean thoroughly with warm soapy water and pat dry using a microfiber cloth.

AFTERCARE

The full curing time of 14 days should be observed before cleaning your newly painted finish. After this time, paintwork can be washed with a mild soap solution and soft cloth. If extra protection is required apply Chalk Paint Lacquer by Annie Sloan.

STORAGE

Store in a cool dry place. Avoid extreme temperatures both low and high and avoid freezing and exposure to frost.

To maximise shelf life decant used tins that are less than half full into smaller, tightly sealed containers.

For best results use within 12 months of purchase.

