

KEY FEATURES

- Compact design for wine cabinets and small wine cellars
- Multiple exhaust configurations*
- Hot side can be ducted*
- Indoor units: -20F** to 95F* temperature range
- 40F temperature differential
- Advanced digital display
- · Electronic temperature control
- Adjustable humidity control
- Comprehensive alarm protection
- Commercial-grade Electrofin coating (evaporator coil)
- ETL Tested and Certified
- Made in the USA
- Warranty: 5 Years (entire system)
- * Excludes 1800XTSr cooling units, which cannot be ducted, and have a maximum intake temperature of 85F
- **Requires compressor heater below 40F, plus fan cycling switch below 20F.



CellarPro 1800 Series cooling units have compact designs, perfect for wine cabinets and small wine cellars up to 400 cubic feet. Except for the 1800XTSr, cold air exhausts from the bottom of the cooling unit and hot air exhausts from your choice of the top or the rear of the cooling unit. The 1800XTSr cold-side airflows are entirely on the bottom of the cooling unit, and the hot side airflows are at the front of the cooling unit. All CellarPro units include electronic temperature and adjustable humidity control, and are significantly quieter than comparable cooling units

SPECIFICATIONS

Model	1800QTL-ECX	1800QT-ECX	1800XT-ECX	1800XTS-ECX	1800XTSr	1800XTSx-EC
Cellar Size (Nominal Cu Ft)*	Cabinet	150	250	400	400	400
Compressor Size (HP)	1/8 Ton	1/6 Ton	1/5 Ton	1/4 Ton	1/4 Ton	1/4 Ton
BTUH @ 55F	1065	1380	1456	1886	1886	1886
CFM	72	72	90	90	102	90
Cooling Unit dBA	41	45	47	54	52	52
Installation Environment	Indoor					Outdoor
Ambient Intake Range	-20** to 95F				-20** to 85F	-20*** to 95F
Power	115V AC / 60Hz					115V AC / 60Hz
Amps (Starting / Running)	14.2 / 2.36	20.1 / 2.89	20.1 / 2.95	22.2 / 3.62	22.2 / 3.45	22.2 / 4.29
Dedicated Circuit	15-Amp					15-Amp
Refrigerant	R134a					R134a
Drain Line	Optional - 1/2" ID Offered at No Charge					Included
Ducting - Cold Side	NO	NO	NO	NO	NO	NO
Ducting - Hot Side	Optional – 6" Diam.				NO	NO
Size (W x D x H - inches) / Weight (lbs)	18 x 16.5 x 10.5 / 60				18w x 19.5d x 10.5h / 70	18.1 x 22 x 10.6 / 70

^{*}Assumes 85F ambient, 55F inside the cellar, and proper cellar construction with R19 insulation throughout.







^{**}Requires a compressor heater below 40F and a fan cycling switch below 20F.

^{***}Compressor heater is included. Requires a fan cycling switch below 20F.