JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 1

Compilation date: 01/08/2008

Revision date: 07/12/2018

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Product code: 304

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: NWT FM Solutions

Units 9 & 10 Brickfields Huyton Business Park

Huyton Liverpool L36 6HY

UK

Tel: +44 (0) 15170 30044 **Fax:** +44 (0) 15170 30055

Email: sales@northwestteas.co.uk

1.4. Emergency telephone number

Emergency tel: NHS 111

NHS Direct Wales 08454647

ROI 01 809 2166

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P280: Wear eye protection, protective gloves. P264: Wash hands thoroughly after handling.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

P405: Store locked up.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

SODIUM HYDROXIDE - REACH registered number(s): 01-2119457892-27-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	10-30%

AMINES, C12-14 (EVEN NUMBERED) -ALKYLDIMETHYL, N-OXIDES - REACH registered number(s): 01-2119490061-47-xxxx

931-292-6	308062-28-4	-	Acute Tox. 4: H302; Skin Irrit. 2: H315;	1-10%	
			Eye Dam. 1: H318; Aquatic Acute 1:		
			H400; Aquatic Chronic 2: H411		

B-ALANINE,N-COCO ALKYL DERIVATIVES, SODIUM SALTS - REACH registered number(s): 01-2119976233-35-xxxx

271-795-1 68608	68-4 -	Eye Irrit. 2: H319	1-10%
-----------------	--------	--------------------	-------

ALCOHOLS C12-C14, ETHOXYLATED, SULPHATED, SODIUM SALTS - REACH registered number(s): 01-2119488639-16-xxxx

-	68891-38-3	-	Eye Dam. 1: H318; Skin Irrit. 2: H315;	1-10%
			Aquatic Chronic 3: H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Drench the affected skin with running water for 10 minutes or longer if substance is still on

skin. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 3

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to

drink immediately. Give 1 cup of water to drink every 10 minutes. Transfer to hospital as soon

as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Transfer to

hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Severe burns may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: May cause permanent damage. Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur. Corrosive burns may appear around the lips. There

may be soreness and redness of the mouth and throat. There may be difficulty swallowing.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Mark

out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

Neutralise with dilute hydrochloric acid.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed.

Suitable packaging: Stainless steel. Polyethylene. Teflon.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Hand protection: Gloves (alkali-resistant).

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Alkali resistant protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Not applicable.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Highly viscous

Boiling point/range°C: 100 Melting point/range°C: 0

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: Not applicable. Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable. Vapour pressure: Not applicable.

Relative density: 1.178

[cont...]

JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 5

pH: 13.5

VOC g/I: 0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Aluminium. Magnesium. Zinc.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide. In combustion emits toxic fumes of

nitrogen oxides.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

B-ALANINE,N-COCO ALKYL DERIVATIVES, SODIUM SALTS

					1
ORL	-	LD50	>5000	mg/kg	ı
			I .	0 0	

ALCOHOLS C12-C14, ETHOXYLATED, SULPHATED, SODIUM SALTS

ORL	RAT	LD50	>2000	mg/kg
OIL	11/71	LD30	/2000	IIIg/kg

Relevant hazards for product:

Llamand	Davita	Pagin
Hazard	Route	Basis

JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 6

Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: May cause permanent damage. Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur. Corrosive burns may appear around the lips. There

may be soreness and redness of the mouth and throat. There may be difficulty swallowing.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

B-ALANINE, N-COCO ALKYL DERIVATIVES, SODIUM SALTS

-	48H EC50	18	mg/l
-	48H EC50	97.5	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable. The surfactants contained in this preparation comply with the biodegradability

criteria as laid down in regulation (EC) No.648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 7

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

(SODIUM HYDROXIDE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

1 LTR; LIMITED QUANTITY FOR ADR

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

[cont...]

JANIT-X PROFESSIONAL HEAVY DUTY DRAIN BUSTER

Page: 8

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.