

Eaton 107013

Catalog Number: 107013

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 90 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Screw terminals DILM170(RAC240)



General specifications

Product Name	Catalog Number
Eaton Moeller® series DILM contactor	107013
Model Code	EAN
DILM170(RAC240)	4015081067817
Product Length/Depth	Product Height
160 mm	170 mm
Product Width	Product Weight
90 mm	2.25 kg
Certifications	Catalog Notes
CSA File No.: 012528 IEC/EN 60947 CSA-C22.2 No. 60947-4-1-14 UL Category Control No.: NLDX VDE 0660 CE IEC/EN 60947-4-1 UL 60947-4-1 UL CSA CSA Class No.: 2411-03, 3211-04 UL File No.: E29096	Contacts according to EN 50012

Number Of Poles

Three-pole

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Catalogs

SmartWire-DT Catalog

Product Range Catalog Switching and protecting motors

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

Switching and protecting motors - catalog

Characteristic curve

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

[eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps](#)

Drawings

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-dilm-dimensions-011.eps](#)

[eaton-contactors-dilm-dimensions-003.eps](#)

[eaton-contactors-dilm-3d-drawing.eps](#)

[eaton-contactors-dilm-3d-drawing-013.eps](#)

eCAD model

[DA-CE-ETN.DILM170\(RAC240\)](#)

Installation instructions

[eaton-dil-contactors-instruction-leaflet-il03407039z.pdf](#)

Installation videos

WIN-WIN with push-in technology

mCAD model

[DA-CD-dil_m80_170](#)

[DA-CS-dil_m80_170](#)

PEP Eco-passport

[EATO-00022-V01.01-EN](#)

System overview

[eaton-contactors-dilm-contactor-system-overview.eps](#)

Wiring diagrams

[eaton-contactors-contact-dilm-wiring-diagram-003.eps](#)

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Suppressor circuit in actuating electronics

Operating frequency

3000 mechanical Operations/h (AC operated)

Pollution degree

3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT

No

Rated impulse withstand voltage (Uimp)

8000 V AC

Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running

Connection

Screw terminals

Frame size

FS4

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

25 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

40 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase

50 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

30 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase

60 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

125 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

125 HP

Conventional thermal current i_{th} (1-pole, enclosed)

415 A

Conventional thermal current i_{th} (3-pole, enclosed)

166 A

Conventional thermal current i_{th} at 55°C (3-pole, open)

190 A

Conventional thermal current i_{th} of main contacts (1-pole, open)

460 A

Equipment heat dissipation, current-dependent P_{vid}

41.1 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

13.7 W

Application

Contactors for Motors

Product category

Contactors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Arcing time

15 ms

Electrical connection type of main circuit

Screw connection

Screwdriver size

2, Terminal screw, Control circuit cables, Pozidriv screwdriver
0.8 x 5.5/1 x 6 mm, Terminal screw, Control circuit cables,
Standard screwdriver

Voltage type

AC

Degree of protection

IP00

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Number of contacts (normally closed) as main contact

0

Number of main contacts (normally open contact)

3

Rated breaking capacity at 220/230 V

1500 A

Rated breaking capacity at 380/400 V

1500 A

Rated breaking capacity at 500 V

1500 A

Rated breaking capacity at 660/690 V

1320 A

Rated control supply voltage (Us) at AC, 50 Hz - max

240 V

Rated control supply voltage (Us) at AC, 50 Hz - min

190 V

Rated control supply voltage (Us) at AC, 60 Hz - max

240 V

Rated control supply voltage (Us) at AC, 60 Hz - min

190 V

Drop-out voltage

AC operated: 0.6 - 0.25 x UC, AC operated

Overvoltage category

III

Duty factor

100 %

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Lifespan, mechanical

10,000,000 Operations (AC operated)

Pick-up voltage

0.8 - 1.15 V AC x Uc

Power consumption, pick-up, 50 Hz

180 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Safe isolation

690 V AC, Between the contacts, According to EN 61140

690 V AC, Between coil and contacts, According to EN 61140

Power consumption, pick-up, 60 Hz

170 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Residual current

1 mA (with actuation of A1 - A2 by the electronics with "0" signal)

Screw size

M3.5, Terminal screw, Control circuit cables

M10, Terminal screw, Main cables

5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables

Power consumption, sealing, 50 Hz

2.3 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

3.1 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Power consumption, sealing, 60 Hz

2.3 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

3.1 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Terminal capacity (stranded)

1 x (16 - 95) mm², Main cables

2 x (16 - 70) mm², Main cables

Terminal capacity (copper band)

2 x (6 x 16 x 0.8) mm (Number of segments x width x thickness),
Main cables

Terminal capacity (flexible with ferrule)

2 x (0.75 - 2.5) mm², Control circuit cables

1 x (10 - 95) mm², Main cables

1 x (0.75 - 2.5) mm², Control circuit cables

2 x (10 - 70) mm², Main cables

Shock resistance

10 g, N/O main contact, Mechanical, according to IEC/EN
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms

10 g, N/O main contact, Mechanical, according to IEC/EN
60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN
60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN
60068-2-27, Half-sinusoidal shock 10 ms

Terminal capacity (solid)

1 x (0.75 - 4) mm², Control circuit cables

2 x (0.75 - 2.5) mm², Control circuit cables

Terminal capacity (solid/stranded AWG)

18 - 14, Control circuit cables

Single 8...3/0, double 8...2/0, Main cables

Switching capacity (main contacts, general use)

225 A, Maximum motor rating (UL/CSA)

Tightening torque

14 Nm, Screw terminals, Main cables

1.2 Nm, Screw terminals, Control circuit cables

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated insulation voltage (Ui)

690 V

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

2100 A

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V

225 A

Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V

170 A

Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

170 A

Rated operational current (Ie) at AC-3, 440 V

170 A

Rated operational current (Ie) at AC-3, 500 V

170 A

Rated operational current (Ie) at AC-3, 660 V, 690 V

100 A

Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V

65 A

Rated operational current (Ie) at AC-4, 400 V

65 A

Rated operational current (Ie) at AC-4, 440 V

65 A

Rated operational current (Ie) at AC-4, 500 V

65 A

Rated operational current (Ie) at AC-4, 660 V, 690 V

50 A

Rated operational current (Ie) at DC-1, 110 V

160 A

Rated operational current (Ie) at DC-1, 220 V

90 A

Rated operational current (Ie) at DC-1, 60 V

160 A

Rated operational current for specified heat dissipation (In)

170 A

Rated operational power at AC-3, 240 V, 50 Hz

57 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

90 kW

Rated operational power at AC-3, 415 V, 50 Hz

100 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

20 kW

Rated operational power at AC-4, 240 V, 50 Hz

22 kW

Rated operational power at AC-4, 380/400 V, 50 Hz

33 kW

Rated operational power at AC-4, 415 V, 50 Hz

39 kW

Rated operational power at AC-4, 440 V, 50 Hz

41 kW

Rated operational power at AC-4, 500 V, 50 Hz

47 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

48 kW

Rated operational power (NEMA)

93 kW

Rated operational voltage (Ue) at AC - max

690 V

Resistance per pole

0.6 m Ω

Static heat dissipation, non-current-dependent Pvs

2.3 W

Stripping length (control circuit cable)

10 mm

Stripping length (main cable)

24 mm

Switching time (AC operated, make contacts, closing delay) -

max

33 ms

Switching time (AC operated, make contacts, closing delay) - min

28 ms

Switching time (AC operated, make contacts, opening delay) - max

41 ms

Switching time (AC operated, make contacts, opening delay) - min

35 ms

Short-circuit current rating (basic rating)

600 A, max. Fuse, SCCR (UL/CSA)

600 A, max. CB, SCCR (UL/CSA)

10 kA, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

65 kA, CB, SCCR (UL/CSA)

250 A, max. CB, SCCR (UL/CSA)

30/100 kA, Fuse, SCCR (UL/CSA)

300/300 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

30/100 kA, Fuse, SCCR (UL/CSA)

30 kA, CB, SCCR (UL/CSA)

350 A, max. CB, SCCR (UL/CSA)

300/600 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating (type 1 coordination) at 400 V

250 A gG/gL

Short-circuit protection rating (type 1 coordination) at 690 V

250 A gG/gL

Short-circuit protection rating (type 2 coordination) at 400 V

250 A gG/gL

Short-circuit protection rating (type 2 coordination) at 690 V

250 A gG/gL

Special purpose rating of ballast electrical discharge lamps

160 A (600V 60Hz 3phase, 347V 60Hz 1phase)

160 A (480V 60Hz 3phase, 277V 60Hz 1phase)

Special purpose rating of definite purpose rating

170 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)

1020 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)

Special purpose rating of elevator control

92 A, 200 V 60 Hz 3-ph, (UL/CSA)
40 HP, 240 V 60 Hz 3-ph, (UL/CSA)
75 HP, 480 V 60 Hz 3-ph, (UL/CSA)
30 HP, 200 V 60 Hz 3-ph, (UL/CSA)
100 HP, 600 V 60 Hz 3-ph, (UL/CSA)
99 A, 600 V 60 Hz 3-ph, (UL/CSA)
104 A, 240 V 60 Hz 3-ph, (UL/CSA)
96 A, 480 V 60 Hz 3-ph, (UL/CSA)

Special purpose rating of refrigeration control (CSA only)

540 A, LRA 600 V 60 Hz 3phase; (CSA)
540 A, LRA 480 V 60 Hz 3phase; (CSA)
90 A, FLA 600 V 60 Hz 3phase; (CSA)
90 A, FLA 480 V 60 Hz 3phase; (CSA)

Special purpose rating of resistance air heating

160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Special purpose rating of tungsten incandescent lamps

160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

Conventional thermal current i_{th} at 40°C (3-pole, open)

225 A

Conventional thermal current i_{th} at 50°C (3-pole, open)

200 A

Conventional thermal current i_{th} at 60°C (3-pole, open)

185 A

Rated operational power at AC-3, 440 V, 50 Hz

105 kW

Rated operational power at AC-3, 500 V, 50 Hz

120 kW

Rated operational power at AC-3, 690 V, 50 Hz

96 kW

Actuating voltage

RAC 240: 190 - 240 V 50/60 Hz

Altitude

Max. 2000 m

Operating voltage at AC, 50 Hz - min

230 V

Operating voltage at AC, 50 Hz - max

690 V

Operating voltage at AC, 60 Hz - min

230 V

Operating voltage at AC, 60 Hz - max

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)