Interlock, mechanical, for DILM80-150

Part no. DILM150-XMV

240081

EL Number 4131011

(Norway)



General specifications	
Product name	Eaton Moeller® series DILM interlock
Part no.	DILM150-XMV
EAN	4015082400811
Product Length/Depth	314 millimetre
Product height	17.2 millimetre
Product width	196 millimetre
Product weight	0.76 kilogram
Certifications	UL File No.: E29096 IEC/EN 60947-4-1 CE CSA UL CSA-C22.2 No. 14-05 UL 508 CSA Class No.: 2411-03, 3211-04 CSA File No.: 012528 UL Category Control No.: NLDX
Product Tradename	DILM
Product Type	Accessory
Product Sub Type	Interlock
Features & Functions	
Fitted with:	Mounting plate for contactor
General information	
Accessory/spare part type	Mechanical locking
Product category	Accessories
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	Not applicable.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

 $Low-voltage\ industrial\ components\ (EG000017)\ /\ Accessories/spare\ parts\ for\ low-voltage\ switch\ technology\ (EC002498)$

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory/spare part	Mechanical locking
Accessory	Yes
Spare part	No