# how to make

# Lincraft











# how to make



# **DIFFICULTY** • • •

Approximate Time of Project: 1hr

# **MATERIALS**

Calico

Fusible heavy interfacing Fabric paint

Bias binding

Fastener snaps

# **EQUIPMENT**

Fabric scissors

Iron

Paint brush

Pins

Sewing machine

### **HELPFUL HINTS**

- 0.5cm seam allowance included in measurements.
- Add more female snap fasteners on the front to allow you to pack the bag smaller or larger depending on the contents.

### **STEPS**

Cut the following;

Calico

- a. Two 21x8cm rectangles for the bottom
- **b.** Four 21x31cm rectangles for the front and back panels
- c. Four 8x31cm rectangles for the sides
- **d.** A 13x3cm rectangle for the closure

# Interfacing:

- a. A 22x9cm rectangle for the bottom
- **b.** Two 22x32cm rectangles for the front and back panels
- c. Two 9x32cm rectangles for the sides
- **2.** Set half of the calico pieces aside for later.
- 3. Iron the interfacing to the corresponding calico pieces.
- **4.** Paint your design onto the interfacing calico pieces. Allow to dry completely before the next step.
- **5.** Pin the remaining calico piece to the interfaced corresponding pieces. Wrong sides together.

- 6. Baste around all the edges to secure.
- Sew all the pieces together so the seams face out on the right side of the bag.
  - a. Pin and sew the side pieces to the front and back panels to all the 31cm sides are joined.
  - **b.** Pin and sew the bottom panel in so the sides of the same length match up.
- **8.** Trim the raw edges of the bag so they are 0.5cm.
- Sew the bias binding down all the 31cm lengths first.Sew the binding around the remaining raw seams at the top and bottom of the bag.

## 10. Make the closure:

- a. Fold the 13x3cm rectangle in half lengthways.
- **b.** Sew around all raw sides leaving a small opening to turn it right side out.
- **c.** Turn the rectangle right side out and topstitch around all sides.
- **d.** Sew a shorted side to the outside of the bag 4cm from the top of the back.
- **e.** Attach a male snap fastener to the other end of the closure.
- f. Attach a female snap fastener to the front of the bag 15cm from the top.
- 11. Pack lunch in the bag and fold the top of the bag down on itself and snap the fasteners together to secure the bag.







