

how to
make

Lincraft



Kids Cable
Jacket Hoodie

#A472

MEASUREMENTS

Years		4-5	6-7	8-10	11-12	13-14
Fits chest	cm	63	68	75	80	85
Garment measures	cm	72	78	84	89	94
Length	cm	46	50	54	56	59
Sleeve length	cm	31	35	40	42	43
Yarn Required:						
Lincraft Coaster	50g balls	9	11	12	14	15

DIFFICULTY ●●●

NEEDLES:

A pair of 5.50mm knitting needles.
Wool needle for sewing up.

REQUIREMENTS:

A cable needle.
6 (7-7-7-8) buttons.

TENSION:

16.5 sts and 22 rows to 10cm over stocking st, using 5.50mm needles.

SPECIAL ABBREVIATIONS:

C4B = slip next 2 sts onto cable needle and leave at back of work, K2, then K2 from cable needle.

C4F = slip next 2 sts onto cable needle and leave at front of work, K2, then K2 from cable needle.

C6B = slip next 3 sts onto cable needle and leave at back of work, K3, then K3 from cable needle.

C6F = slip next 3 sts onto cable needle and leave at front of work, K3, then K3 from cable needle.

BACK

Using 5.50mm needles, cast on 61 (67-71-75-79) sts.

1st row: K2, * P1, K1, rep from * to last st, K1.

2nd row: K1, * P1, K1, rep from * to end.

Last 2 rows form rib.

Work a further 5 (7-9-9-9) rows rib.

Next row: Rib 17 (20-22-24-26), [inc in next st, rib 1] 4 times, rib 10, [inc in next st, rib 1] 5 times, rib 16 (19-21-23-25) ... 70 (76-80-84-88) sts.

Beg Cable Patt:

1st row: P16 (19-21-23-25), K2, C4F, P2, K6, P10, K6, P2, C4B, K2, P16 (19-21-23-25).

2nd row: K16 (19-21-23-25), P6, K2, P6, K10, P6, K2, P6, K16 (19-21-23-25).

3rd row: P16 (19-21-23-25), C4B, K2, P2, C6F, P10, C6B, P2, K2, C4F, P16 (19-21-23-25).

4th row: K16 (19-21-23-25), P6, K2, P6, K10, P6, K2, P6, K16 (19-21-23-25).

Last 4 rows form cable patt for Back.

Cont in cable patt until work measures 31 (33-35-36-38) cm from beg, working last row on wrong side.

Shape Armholes:

Keeping cable patt correct, cast off 4 (5-5-6-6) sts at beg of next 2 rows ... 62 (66-70-72-76) sts.

Dec one st at each end of next row, then every alt row until 54 (58-60-62-64) sts rem.

Cont in cable patt without shaping until work measures 46 (50-54-56-59) cm from beg, working last row on wrong side.

Shape Shoulders:

Cast off 6 (6-6-7-7) sts at beg of next 4 rows, then 6 (7-7-6-7) sts at beg of next 2 rows.

Cast off rem 18 (20-22-22-22) sts, knitting or purling sts as they appear.



LEFT FRONT

Using 5.50mm needles, cast on 29 (31-33-35-37) sts.
Work 7 (9-11-11-11) rows rib.

Next row: Rib 4 (3-3-3-3), [inc in next st, rib 1] 4 (5-5-5-5) times, rib 17 (18-20-22-24) ... 33 (36-38-40-42) sts.

Beg Cable Patt:

1st row: P16 (19-21-23-25), K2, C4F, P2, K6, P3.

2nd row: K3, P6, K2, P6, K16 (19-21-23-25).

3rd row: P16 (19-21-23-25), C4B, K2, P2, C6F, P3.

4th row: K3, P6, K2, P6, K16 (19-21-23-25).

Last 4 rows form cable patt for Left Front.

Cont in cable patt until work measures same as Back to beg of armhole shaping, working last row on wrong side.

Shape Armhole:

Keeping cable patt correct, cast off 4 (5-5-6-6) sts at beg of next row ... 29 (31-33-34-36) sts.

Dec one st at armhole edge in every alt row until 25 (27-28-29-30) sts rem.

Cont without shaping until there are 13 rows less than Back to beg of shoulder shaping, working last row on right side.

Shape Neck:

Cast off 4 (5-5-5-5) sts, patt to end ... 21 (22-23-24-25) sts.

Dec one st at neck edge in next row, then every 4th (4th-alt-alt-alt) row until 19 (20-21-22-23) sts rem, then every 6th (6th-4th-4th-4th) row until 18 (19-19-20-21) sts rem.

Work 1 row.

Shape Shoulder:

Cast off 6 (6-6-7-7) sts at beg of next and alt row.

Work 1 row.

Cast off rem 6 (7-7-6-7) sts.

RIGHT FRONT

Using 5.50mm needles, cast on 29 (31-33-35-37) sts.
Work 7 (9-11-11-11) rows rib.

Next row: Rib 17 (18-20-22-24), [rib 1, inc in next st] 4 (5-5-5-5) times, rib 4 (3-3-3-3) ... 33 (36-38-40-42) sts

Beg Cable Patt:

1st row: P3, K6, P2, C4B, K2, P16 (19-21-23-25).

2nd row: K16 (19-21-23-25), P6, K2, P6, K3.

3rd row: P3, C6B, P2, K2, C4F, P16 (19-21-23-25).

4th row: K16 (19-21-23-25), P6, K2, P6, K3.

Last 4 rows form cable patt for Right Front.

Cont in cable patt until work measures same as Back to beg of armhole shaping, working last row on wrong side.

Work 1 row.

Shape Armhole:

Keeping cable patt correct, cast off 4 (5-5-6-6) sts at beg of next row ... 29 (31-33-34-36) sts.

Dec one st at armhole edge in next row, then every alt row until 25 (27-28-29-30) sts rem.

Cont without shaping until there are 14 rows less than Back to beg of shoulder shaping, working last row on wrong side.

Shape Neck:

Cast off 4 (5-5-5-5) sts, patt to end ... 21 (22-23-24-25) sts.

Work 1 row.

Dec one st at neck edge in next row, then every 4th (4th-alt-alt-alt) row until 19 (20-21-22-23) sts rem, then every 6th (6th-4th-4th-4th) row until 18 (19-19-20-21) sts rem.

Work 2 rows.

Shape Shoulder:

Cast off 6 (6-6-7-7) sts at beg of next and alt row.

Work 1 row.

Cast off rem 6 (7-7-6-7) sts.

SLEEVES

Using 5.50mm needles, cast on 31 (31-33-35-35) sts.

Work 7 (9-11-11-11) rows rib.

Next row: Rib 10 (8-9-10-10), [rib 1, inc in next st] 5 (7-7-7-7) times, rib 11 (9-10-11-11) ... 36 (38-40-42-42) sts.



Beg Cable Patt:

1st row: P7 (8-9-10-10), K6, P2, C4B, K2, P2, K6, P7 (8-9-10-10).

2nd row: K7 (8-9-10-10), P6, K2, P6, K2, P6, K7 (8-9-10-10).

3rd row: P7 (8-9-10-10), C6B, P2, K2, C4F, P2, C6F, P7 (8-9-10-10).

4th row: K7 (8-9-10-10), P6, K2, P6, K2, P6, K7 (8-9-10-10).

Last 4 rows place cable patt for Sleeves.

Keeping cable patt correct as placed and working extra sts into reverse stocking st, inc one st at each end of next row, then every 6th (8th-8th-6th-6th) row until there are 40 (44-46-48-48) sts, then every 8th (10th-10th-8th-8th) row until there are 50 (52-56-58-62) sts.

Cont in cable patt without shaping until work measures 31 (35-40-42-43) cm (or length desired) from beg, working last row on wrong side.

Shape Top:

Keeping cable patt correct, cast off 2 (3-3-3-3) sts at beg of next 2 rows ... 46 (46-50-52-56) sts.

Dec one st at each end of next row, then every alt row until 34 (30-28-28-36) sts rem, then every row until 8 (8-10-10-10) sts rem.

Cast off.

RIGHT FRONT BAND FOR GIRL OR LEFT FRONT BAND FOR BOY

With right side facing and using 5.50mm needles, knit up 67 (73-79-79-91) sts along front edge.

Work 1 (1-3-3-3) row/s rib, beg with a 2nd row.

Next row: Rib 2, rib 2tog, yrn, * rib 10 (9-10-10-10), rib 2tog, yrn, rep from * to last 3 sts, rib 3 ... 6 (7-7-7-8) buttonholes.

Work 3 rows rib.

Cast off in rib.

LEFT FRONT BAND FOR GIRL OR RIGHT FRONT BAND FOR BOY

Work to correspond with other Front Band, omitting buttonholes.

HOOD

Using 5.50mm needles, cast on 95 (99-103-105-109) sts.

Work 4 (4-6-6-6) rows rib and inc one st in centre of last row ... 96 (100-104-106-110) sts.

Work in reverse stocking st until work measures 16 (17-18-19-20) cm from beg, ending with a knit row.

Shape Back Of Hood:

Next row: P48 (50-52-53-55), turn.

** Cont on these 48 (50-52-53-55) sts.

Dec one st at inside edge in every row until 43 (45-47-48-50) sts rem.

Cast off loosely purlways. **

Join yarn to rem sts and purl to end.

Rep from ** to **.

FINISHING

Join shoulder, side and Sleeve seams. Sew in Sleeves.

Join centre back seam of Hood. Sew Hood in position, beg and ending at edge of Front Bands. Sew on buttons.

Sew in all ends.

