

PN: H223111621



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808
Fax: (504) 733-2996
PalmerSafetyUS.com

TECHNICAL SPECIFICATIONS

Harness 5pt., QCB, Padded Back and Legs, Back D-Ring, Side D-Rings with Positioning Belt, Black Color.



AKULA
HARNESS SERIES

3 D-ring harness with 5 points of easy adjustability, quick connect chest and leg buckles with roller cam torso, sewn-in back and leg moisture wicking padding, form-fit positioning construction belt, built-in srl back plate tunnel for personal self-retracting lifeline, heavy duty tag and impact indicators. Meets or exceeds the performance standards of ANSI Z359.11-2014 and A10.32-2012.



MOISTURE WICKING PADDING



USER CAPACITY: 130 - 420 lbs.

- DESIGN:**
- Back dorsal D-Ring for fall arrest
 - SRL back plate tunnel for personal self-retracting device
 - Work positioning side (hip) D-rings
 - Quick connect chest and leg buckles with roller cam torso
 - Breakaway lanyard keepers
 - Built-in construction belt

WEBBING: Material: Polyester | Width: 1.73 in. ± 0.008 in. (44mm ± 0.2mm)
Breaking Strength: 5000 lbs. (Min.)

STITCHING THREAD: Material: High Tenacity Polyester

METAL COMPONENT: Material: Aluminum | Finish: Powder Coated

CONFORMS TO: Meets or Exceeds ANSI Z359.11-2014

HARNESS WEIGHT: 5.89 lbs. ± 0.02 lbs.

Part #	Size
H223111621.MD	Medium
H223111621.LG	Large
H223111621.XL	X-Large