



Safety Rail Source®

NEXTGEN FLOOR HATCH RAILING™

CUT SHEET

The NextGen Floor Hatch Safety Railing™ is designed for safe ingress and egress through access hatches and for fall protection at floor hatch openings. It meets OSHA Standards CFR 29 1910.23 and 29 CFR 1910.66. It is easy to install with a simple hex key.

Our floor hatch railing kits can be ordered in galvanized or aluminum and can be painted the color of your choice. The railing kit is made of Kee Klamp® fittings and is shipped in components. You can choose either 1 ¼" or 1 ½" galvanized or aluminum pipe for your railing.

For a standard installation, drill 2 holes for each base fitting and secure with 3/8" anchors. If you require the railing to be removed for a flat surface, select the type 66 ground socket base fittings. Type 66 fittings mount flush to the floor surface. All fitting set screws must be tightened to 29 ft/lbs.

The 2-sided kit can be ordered if the floor hatch backs up to the wall. Our floor hatch safety railing can be ordered with toe plates if desired.



**3-Sided
Floor Hatch Railing**



**2-Sided
Floor Hatch Railing**



**Type 62 Base Fitting
Surface Mount**



**Type 66 Base Fitting
Flush Mount**



Made in USA

Safety Rail Source®
2570 Blvd of the Generals, Ste.200
Norristown, PA 19403
(877) 723-3766
www.SafetyRailSource.com