



Safety Rail Source®

KEEHATCH® RAILING

PRODUCT FLIER

Safety Rail Source® offers the original Roof Hatch Guardrail with a Self-Closing Gate. OSHA requires roof access points to be protected by a standard railing and gate. When the hatch is open, the guardrail, gate and roof hatch door together will protect your roof access points by surrounding the opening, thereby mitigating the risk of falling through the open hatch. In addition, railings provide safe egress and ingress through roof hatches.

Railings are available in either galvanized steel or aluminum. The aluminum KeeHatch® Mightylight (KHML) models are ideal for harsher environments. We offer over 80 OSHA Compliant models for every size of access hatch.

KeeHatch® requires no special tools or training to install and step-by-step instructions are provided. The modular design makes it easy to make any adjustments on site. It's suitable for all new roof hatches and easily integrates with existing hatches.

Features:

- Protects workers while hatch is open
- Self-closing safety gate ensures safety around the entire opening
- Fits all hatches
- Mounts to counter flashing or curb
- Easy to install
- Mounting hardware included

OSHA Compliance:

Exceeds OSHA requirements for railings according to OSHA Standards 29 CFR 1910.23, 29 CFR 1910.27, and 29 CFR 1910.28(b)(3)(v)(A).

Standard Galvanized Models:

RHSR-SS 3630 - 36"x30" Hatch*
RHSR-FB 3054 - 30"x54" Hatch*
RHSR-FB 4896 - 30"- 48"x96" Hatch*
RHSR-O 4848 - 48"x48" Hatch*

**Inside curb dimension*



Standard Aluminum Models:

KHML-SS 3630 - 36"x30" Hatch*
KHML-FB 3054 - 30"x54" Hatch*
KHML-FB 4896 - 30"- 48"x96" Hatch*
KHML-O 4848 - 48"x48" Hatch*

Contact us for custom models and sizes.

Safety Rail Source®
2570 Blvd of the Generals, Ste. 200
Norristown, PA 19403
(877) 723-3766
www.SafetyRailSource.com