

Safety Rail Source®

NEXTGEN 3000[™] KART-A-RAIL

PRODUCT FLIER

Safety Rail Source[®] has developed a portable 'railings on a cart' system that is perfect for easily transporting rails and bases wherever needed on the rooftop, grounds and facilities. It holds 11 rails of any size, and 12 bases (rails and bases purchased separately). NextGen 3000[™] Universal Railing is used to protect workers from falling off a roof or to protect machinery, open holes and to restrict access to danger zones.

Features

- Racks to carry up to 11 rails and 12 bases
- 4 lifting points for craning to rooftop
- Easy pull handle
- Hand brake
- Balloon type puncture-proof tires
- Finished with durable TS22 Safety Yellow coating.

<u>Assembly</u>

- Mount wheels onto cart frame
- Attach deck to cart
- Attach pull handle
- Bolt railing racks to cart frame
- Load railings and bases to cart









Safety Rail Source[®] 2570 Blvd of the Generals, Ste. 200 Norristown, PA 19403 (877) 723-3766 www.SafetyRailSource.com



Safety Rail Source®

NEXTGEN 3000[™] KART-A-RAIL


NextGen 3000[™] Universal Guardrail is a state-of-the-art, non-penetrating, modular rooftop safety railing system. Due to its patented engineering and design, NextGen 3000 outperforms all other roof fall protection systems. When force is applied to the top safety rail the lightweight, easy to carry, 58-pound bases drive the load downward and grip into the roof. This enables the safety rail system to meet OSHA requirements while not penetrating the roof membrane. Installation is fast and easy.



Lightweight 58 lb. Bases



Durable TS-22 Coating



15 Standard Colors to Choose



Galvanized Option

Safety Rail Source[®] 2570 Blvd of the Generals, Ste. 200 Norristown, PA 19403 (877) 723-3766 www.SafetyRailSource.com






Safety Rail Source®

NEXTGEN 3000[™] KART-A-RAIL

NextGen 3000[™] Universal Rails are available in pre-assembled 5 ft. (14 lbs.), 7.5 ft. (21 lbs.) and 10 ft. (29 lbs.) steel panels. The rails are available in TS-22 Coating or Galvanized finish (custom colors also available). All rail panels are 42" in height and insert into the NextGen 3000[™] Universal Bases. Panels are fastened with hitch pins. Minimum 5 ft. returns are required at terminations per OSHA Standards.



Roof Edge Railing

Materials

- 58 lb. Steel Bases
- 1.66 OD Steel Panels
- TS-22 Durable Coating
- Zinc Plated Hitch Pins
- Neoprene Rubber Pads



Stack Pallet Shipping

Options

- Rolling Gate
- Metal Toe Plate
- 15 Colors
- Adjustable Rails
- Base Dolly



Roof Edge Railing

Made in USA



- Clear debris
- Place Base on Roof
- Insert Panels into Base
- Secure With Hitch Pins
- Install 5 ft. Returns



Skylight Railing

Safety Rail Source[®] 2570 Blvd of the Generals, Ste. 200 Norristown, PA 19403 (877) 723-3766 www.SafetyRailSource.com