



Safety Rail Source®

KEEHATCH® RAILING

SUBMITTAL (FOR ALL MODELS)

Product Description: KeeHatch® Roof Hatch Railing by Safety Rail Source® for safe egress and ingress through roof type access hatches and for protection of roof opening while roof hatch is up. Meets OSHA Standard CFR 29 1910.23 and CFR 29 1910.27. Railing is 42" high and meets OSHA load requirements.

Product Selection Criteria: Please include inside dimensions of your roof hatch with your request so we can select the appropriate model for your needs. Specify standard Galvanized or Aluminum finish.

Type of Installation: Permanent bolt on installation of right and left handed railings, guard railings, mid railings and gate as per supplied instructions and hardware.

Materials:

- **Mounting Brackets:** Kee Klamp® fittings #161-7 or #162-7.
- **Pipe:** 1 ¼" ID A53 Grade B seamed steel or 5/8" OD A500 seamed tube.
- **Finish:** Galvanized.
- **Gate System:** Gate is self closing type. (Chains are no longer OSHA compliant.)
- **Pipe caps:** weather and light resistant vinyl 1/ ½" deep and to fit snugly over pipe ends, or Kee Klamp® 77-7 plugs.
- **Bolts and washers:** Hex head bolts 3/8" x 2 ½ or 1 1/4" grade Z, zinc plated. Fender washers for inside of hatch curb or counter flashing and standard flat washers outside.
- **Railing fittings:** By Kee® Industrial Products

Sealant for brackets: Brackets shall be sealed per roof manufacturers' approved methods. Preferably, the brackets should be installed on the counter flashing where possible.

Labels: Safety no hoisting warning with manufacturer identification & patent number.

Installation: KeeHatch® Railing Systems must be installed according to Safety Rail Source® installation instructions provided in each kit.

Warranty: 7 years; manufacturer's parts only warranty.

Manufactured by: Safety Rail Source® Norristown, PA (877) 723-3766. Patent No. 6,167,659



Safety Rail Source®
2570 Blvd of the Generals, Ste. 200
Norristown, PA 19403
(877) 723-3766
www.SafetyRailSource.com