

Airflow	Hi: 3,662 CFM / Med: 3,336 CFM / Low: 2,986 CFN
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 2,730 CFM / Med: 2,390 CFM / Low: 2,100 CFN
Energy Use	Hi: 377 Watts / Med: 280 Watts / Low: 202 Watts
Recommended SQFT Coverage @ 2-3 CFM per SQF	T Covers 1,181 SQFT to 1,771 SQFT
Amps	Hi: 4.97 / Med: 3.69 / Low: 2.72
Motor Voltage	120VAC, 60 Hz
f of Speeds	3
Minimum Attic Clearance	36"
Duct Diameter	20"
Duct Length	9 feet
Motor Head Diameter	24.75"
Damper Box	Barometric Pressurized R5 Dampers 14" x 30"
Controls	IT-36002 QuietCool RF Wireless Control Kit
Warranty	15 Years
- Framing: Roof Rafter	24" on center
Framing: Ceiling Joist	16" on center
Flashing Dimensions	36" × 36"
Roof Cap Dimensions	39.5" x 39.5"
Overall Height	15"
Roof Opening	22" circle
Removable Grille Outer Dimension	16" × 32"
Ceiling Rough Opening	14.25" × 30.25"
Shipping Package 1: Fan	69 lbs.
Shipping Package 2: Accessories	41 lbs.
Box Dimensions: Fan	42" × 20" × 44"
Box Dimensions: Accessories	36" × 24" × 24"
n The Box	-RM WHF-4.0 Fan -Accessory Bag
	-9 Foot Duct -Removable Grille
	-Damper Box -Cut-out Template
	-RF Wireless Control Kit



