

Low Voltage Cable



PRODUCT SPECIFICATIONS

AWG	18 AWG / 7 Strand Bare Copper
Conductors	2
Insulation	PVC - Plenum
Color Code	Black, Red
Jacket	White / Plenum
Nominal Wall	0.013"
Nominal OD	0.162"
Temperature Rating	75°C
Operating Volts	300V
Print	18 Awg CMP or CL2P or FPLP 75C (ETL) US 2 COND

Certifications

NEC 725-2 (B), Class 2 circuits.
UL Standard 444 Forth Edition July 11, 2008. Revision July 17, 2008.
Meets NEC Article 725 & 800.

Applications

For use in air plenums without conduit for low voltage LED lighting, burglar alarm systems, computers, remote signaling, control and power limited circuits.

PRODUCT DIMENSIONS



ORDERING INFORMATION

Part Number	Description	BX
CL-CBL-CMP-18/2-WH	18/2 Stranded Non-Shielded Plenum	500'



CLEANLIFE®

1-800-316-2532

info@cleanlife.com

www.cleanlife.com

CLEANLIFE®, Finding a Better Way®, and the Pinwheel Mark are registered trademarks of Superior Ventures LLC. All Rights Reserved. Not to be reproduced or published without prior permission.

PLEASE NOTE: Product specifications are based off of third party test reports and are subject to change without notice.

