

Parking Garage LED Canopy Light



shown in dark bronze



shown in white

FEATURES

- 155° Beam pattern for uniform light distribution over large area
- Strong heat dissipation with external airflow fins
- UV resistant lens and coating
- 3/4" hub size, suitable for pole mount without using an adapter
- Motion sensor and photocell option available
- Surface Mount
- IP65 Weatherproof
- 0~10V Dimmable
- 120~277V AC Input
- Lifetime: 50,000+ hrs.
- Mounting Accessories Included
- UL, FCC, DLC and DLC Premium Certified

Color Temperature



4000K



Finish



Matte White Dark Bronze



PRODUCT DIMENSIONS



Size	(A) MM / IN	(B) MM / IN
8.5"	215.9 / 8.5	119.1 / 4.69
10"	254 / 10	119.1 / 4.69

APPLICATION INFORMATION

Applications

- Outdoor

Market Segments

- Commercial
- Parking Garage

ORDERING INFORMATION

Part Number	Size	Color Temperature	Finish	Average Rated Life (hrs.)	Input Voltage	Rated Power	Typical Lumens	Nominal Lumens Per Watt (±3%)	CRI
CL-GCP0840-40W-G-40K	8.5"	4000K	Bronze/White	50,000+	120V AC	40W	4800lm	120	80+
CL-GCP1070-60W-G-40K	10"	4000K	Bronze/White	50,000+	120V AC	60W	7200lm	120	80+
CL-GCP1070-70W-G-40K	10"	4000K	Bronze/White	50,000+	120V AC	70W	8400lm	120	80+

CLEANLIFE®

1-800-316-2532

info@cleanlife.com

www.cleanlife.com

CLEANLIFE® and the Pinwheel Mark are registered trademarks of Superior Ventures LLC. All Rights Reserved. Not to be reproduced or published without prior permission.

PLEASE NOTE: Product specifications are based off of third party test reports and are subject to change without notice.

