LED Flood Light







- 100~277VAC Universal Input
- Long Lifetime, L70>50,000 Hours
- Instant On, No Flicker, Mercury Free, No UV
- High Efficacy, Up to 110 Lumens Per Watt
- Die-Cast Aluminum Housing, Tempered Glass Lens
- Wall Mount or Trunnion Mount Options
- Operating Temperature from -40°F to +122°F
- IP-65 Rated for Wet and Humid Environments
- 5-Year Manufacturer's Limited Warranty
- ETL Listed, DLC Certified & RoHS Compliant











5-Year Limited Warranty

SPECIFICATIONS					
Dimensions	See Table				
Operating Temp.	-40°F (-40°C)~+122°F (+50°C)				
Wattage (±10%)	10W, 30W, 50W, 80W				
Lumens at 5000K	10W=1100lm, 30W=3300lm 50W=5500 lm, 80W=8800				
Efficacy at 5000K	110 LPW				
Color Accuracy	CRI>70				
IP-Rating	IP-65				

APPLICATION INFORMATION

Applications

- Parking Lots
- Walkways
- Garages
- Loading Docs
- Outdoor Signs
- Billboard
- General Area Lighting

Market Segments

- Residential
- Commercial
- Outdoor

Color Temperature

3000K 4000K 5000K











Specifications & Data



Project/Job	Notes
Date	
Comments	
Prepared by	


Ordering Information


CL	FL	40	Wattage	Input Voltage	Color Temperature	Mounting	Dimming
CL	FL	40	10W 30W 50W 80W	120 (120~277Vac)	30K (3000K) 40K (4000K) 50K (5000K)	A (Type A) B (Type B)	N (Non Dimmable) DCD (0~10V Dimmable) ACD (Dimmable)
CL	FL	40	XXW	120	XXK	X	N

Example Part Number: CL-FL-40-80W-120-50K-A-N

Flood Light Dimensions

Part Number	(A) (in./mm)	(B) (in./mm)	(C) (in./mm)	(D) (in./mm)
CL-FL-40-10W-120-XXK-X-X	4.65/118	4.06/104	7.17/182	2.6/66
CL-FL-40-30W-120-XXK-X-X	5.67/144	4.96/126	7.95/202	3.15/80
CL-FL-40-50W-120-XXK-X-X	7.17/182	6.1/155	9.13/232	3.46/88
CL-FL-40-80W-120-XXK-X-X	8.07/205	6.69/170	11.69/297	4.17/106





Installation Options





Mounting Adapter Accessories







TYPE B
Trunnion
CL-FL-BRK-B-1

CLEANLIFE® LED

1-800-316-2532 support@cleanlife.com www.cleanlife.com

CLEANLIFE® and the Pinwheel Mark are registered trademarks of Superior Ventures LLC. All Rights Reserved. Not to be reproduced or published without prior permission.

PLEASE NOTE: Product specifications are based off of third party test reports and are subject to change without notice.

