

SONIC 120

(120L Tank Ultrasonic Cleaner)



FEATURES & BENEFITS

- Multiple Frequency: (a) 25 kHz (b) 40 kHz (c) 72 kHz (d) 104 kHz
- Temperature: 50°C ~ 90°C
- Performance: speeds up the degreasing, passivation, derusting and cleaning process to give a fast turn around of part ready for re-processing.
- Environmental: No hazardous chemicals or noisy mechanical methods.
- Precise: Remove oil or dirt, leaving paint and decorative features intact.
- Adaptability: Safe and effective on a wide variety of applications.
- Passivation chemicals is comply to standard: a) AMS 2700, Method 2 (Aerospace)
b) ASTM A967 (Industrial - Citric Passivation)

USES / APPLICATION

- Automotive
- Marine
- Electronic
- Aerospace / Defence military
- Offshore / Oil & Gas
- Restoration, refurbishment or preservation components
- Pharmaceutical & Health Care
- Medical
- Machining
- Plastic Mould / Stamping Parts
- Degreasing / Derusting
- Passivation
- Plating
- MRO
- Workshop
- Productions
- Maintenance
- Heat Exchanger Descaling



Before

After

Before

After

TANK CAPACITY

- Overall Dimension
1460mm (L) x 1030mm (W) x 1480mm (H)
- Working Dimension
600mm (L) x 500mm (W) x 400mm (H)
- Volume: 120L

PRODUCT CODE