



1. INTRODUCTION

A clear lubricant formulated primarily for dynamic chain applications, where a black, bituminous based product is unacceptable.

SAS18 – 500ml Aerosol

2. WHERE TO USE

Designed for use on all types of industrial metal chains, conveyors, drives, pins, bushes, etc. It has been specifically formulated to provide outstanding lubricating performance under conditions of extreme load. It is able to penetrate areas of difficult access, and when dried, to adhere tenaciously to moving equipment, where it's extremely high viscosity and track prevents "throw-off" caused by centrifugal forces.

3. WHERE NOT TO USE

- On non metallic surfaces.

4. BENEFITS

- High resistance to "throw-off".
- Outstanding lubrication properties under dynamic conditions.
- Resists and prevents corrosion.
- Able to resist pressure cleaning.
- Excellent water resistance.
- Contains extreme pressure additive.

5. PHYSICAL PROPERTIES (Lubricant base except where stated).

Appearance	A clear, yellow coloured liquid.
pH	Not applicable.
Specific Gravity	0.855 +/- 0.007 @ 20 C.
Non Volatiles % m/m	70 – 80
Active Content % m/m, as supplied	30 – 50
Viscosity	Thin liquid, which dries to a thick sticky stringy grease.
Flammability, as supplied	Extremely flammable, flash point below -20 C
Composition Data, as supplied	A suspension of naphthenic oils petroleum wax, polyisobutylenes and extreme pressure additives in Nphtha (petroleum), hydrotreated light and butane/isobutene/propane propellents.
Service Temperature (Continuous)	100 C
Service Temperature (Intermittent)	100 C

6. APPLICATION DETAILS

Shake can thoroughly before use. Hold upright, and spray from a distance of 10 to 20cm. Allow to dry prior to restarting equipment.