

SAFETY DATA SHEET SAS220 EXHAUST REPAIR PUTTY

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SAS220 Exhaust Repair Putty

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Nina Works,

Gelderd Road, Leeds

LS12 6NA

Tel: +44 (0) 113 213 4300

1.4. Emergency telephone number

Emergency telephone +44 (0) 113 213 4300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

SAS220 EXHAUST REPAIR PUTTY

Precautionary statements P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

Contains Sodium Silicate

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Sodium Silicate 10-30%

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove affected person from source of contamination. Get medical attention. Show this

Safety Data Sheet to the medical personnel.

Ingestion Rinse mouth thoroughly with water. Get medical attention. Show this Safety Data Sheet to the

medical personnel.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if any discomfort continues.

Eye contact Wash with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if

any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information Treat symptomatically.

Inhalation May cause irritation. Coughing, chest tightness, feeling of chest pressure.

Ingestion May cause irritation. Sore throat.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

SAS220 EXHAUST REPAIR PUTTY

Eye contact May cause irritation. Redness. Profuse watering of the eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

Toxic gases or vapours.

products

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Avoid inhalation of dust.

For emergency responders Approach the spillage from upwind.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning upCollect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Do not use in

confined spaces without adequate ventilation and/or respirator. Avoid inhalation of dust and

vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep container tightly sealed when not in use. Keep

only in the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No data available.

8.2. Exposure controls

SAS220 EXHAUST REPAIR PUTTY

Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection Wear eye protection.

Hand protection Wear protective gloves.

Other skin and body

protection

Wear protective clothing.

Hygiene measures Provide eyewash station and safety shower.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. In case of possible

exposure to degradation products, use suitable respiratory protection.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Putty. Paste.

Colour Black.

Odour Slight.

pH (concentrated solution): 10.5

Evaporation rate Not available.

Relative density 1.85

Soluble in water.

Viscosity Viscous

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Heat, sparks, flames.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition Thermal decomposition or combustion products may include the following substances: Toxic

products gases or vapours.

SECTION 11: Toxicological information

SAS220 EXHAUST REPAIR PUTTY

11.1. Information on toxicological effects

Inhalation May cause irritation. Coughing, chest tightness, feeling of chest pressure.

Ingestion May cause discomfort. Sore throat.

Skin contact May cause irritation. Redness.

Eye contact May cause eye irritation. Redness. Profuse watering of the eyes.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Collect and place in suitable waste disposal containers and seal securely. Confirm disposal

procedures with environmental engineer and local regulations.

SECTION 14: Transport information

14.1. UN number

3262

14.2. UN proper shipping name

CORROSIVE SOLID, BASIC, INORGANIC, N.O.S., (SODIUM SILICATE)

14.3. Transport hazard class(es)

8

14.4. Packing group

ı

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

SAS220 EXHAUST REPAIR PUTTY

ADR transport category 1

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Revision date 07/05/2015

Revision 1

SDS number 4877

Hazard statements in full H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.