



1. INTRODUCTION

A highly volatile, fast drying solvent based heavy duty degreaser designed to remove dust, greases and oils from automotive components

SAS2 - 500 ml Aerosol

2. WHERE TO USE

On all functional components in automotive brake or clutch assemblies, including callipers, discs, clutch plates etc.

3. WHERE NOT TO USE

- On decorative substrates, where coatings may be affected
- On plastics or rubber components

4. BENEFITS

- Powerful spray, fast evaporating formula
- Cleans Brake and clutch parts without the need for dismantling
- Dissolves and removes brake fluid, grease, oil and dust
- Eliminates brake squeal.
- Eliminates clutch slip caused by contaminated components.

5. PHYSICAL PROPERTIES

Appearance	Clear water white aerosol mist with a characteristic organic odour and extremely fast drying properties.
pH	Not applicable, non-aqueous.
Specific Gravity	0.705 – 0.720 [Base Component]
Non Volatiles % m/m	0
Active Content % m/m	100
Flammability	Extremely flammable, flash point below -20°C
Composition Data, descriptive	A blend of low boiling point hydrocarbons, ketone and alcohol solvents propelled by a hydrocarbon blend.

6. APPLICATION DETAILS

Place a drip tray underneath the work area. Shake Well. Hold can upright. Spray liberally onto the surface to be treated, and allow contaminated liquid to drain into the tray. Agitation with a brush will assist in the removal of heavy or stubborn contamination. Flush spray until all contamination has been removed, and wipe away excess with a soft clean cloth. Always work under well ventilated conditions, taking care to avoid vapour inhalation.