



**Tie Down Strap, 5.5'L x 1"W, 500 lb. Load Limit,
Adjustable Cam Buckle**



Tie Down Strap perfect for securing cargo to shelving brackets in ISO Containers. Tie Down Straps are cut to fit between the lower end of bracket and the lower O-ring and secure the respective bracket in during transport. They have been sized to provide sufficient length to tighten during installation, and minimize impact on space.



BOTTOM, ZINC PLATED CAST CAM BUCKLE



FRONT, ZINC PLATED CAST CAM BUCKLE



SB1206
Tie Down Strap, 5.5'L x 1"W, 500 lb. Load Limit,
Adjustable Cam Buckle

082520-R00

ISO 9001



**CERTIFIED QUALITY
MANAGEMENT SYSTEM**

66' L X 1" W WEB STRAP INFORMATION

Length		Width		Breaking Strength		Working Load Limit	
in	mm	in	mm	Lbs	Kgs	Lbs	Kgs
66	1676.4	1	25.4	500	226.8	500	226.8
Tare Weight - .5lbs / .23kg							
Standard Color: Black							

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS