



Data Sheet


Economy Tie Wraps

PART NUMBER	COLOR	LENGTH INCH/MM	WIDTH INCH/MM	THICKNESS INCH/MM	TIE TENSILE	MAX BUNDLE DIAMETER	PER BAG	PER CASE
EC04-N	NATURAL	4.0/100.0	.098/2.50	.042/1.07	18 lb.	.875	1000	10,000
EC04-B	BLACK	4.0/100.0	.098/2.50	.042/1.07	18 lb.	.875	1000	10,000
EC05-N	NATURAL	5.5/142.0	.098/2.50	.052/1.34	18 lb.	1.35	1000	10,000
EC05-B	BLACK	5.5/142.0	.098/2.50	.052/1.34	18 lb.	1.35	1000	10,000
EC06-N	NATURAL	5.5/142.0	.125/3.20	.055/1.41	40 lb.	1.35	1000	10,000
EC06-B	BLACK	5.5/142.0	.125/3.20	.055/1.41	40 lb.	1.35	1000	10,000
EC07-N	NATURAL	8.0/203.0	.098/2.50	.050/1.28	18 lb.	2.150	1000	10,000
EC07-B	BLACK	8.0/203.0	.098/2.50	.050/1.28	18 lb.	2.150	1000	10,000
EC08-N	NATURAL	7.5/190.0	.188/4.80	.058/1.49	50 lb.	2.060	1000	10,000
EC08-B	BLACK	7.5/190.0	.188/4.80	.058/1.49	50 lb.	2.060	1000	10,000
EC09-N	NATURAL	8.0/203.0	.125/3.20	.055/1.41	40 lb.	2.150	1000	10,000
EC09-B	BLACK	8.0/203.0	.125/3.20	.055/1.41	40 lb.	2.150	1000	10,000
3M17-N	NATURAL	17.0/434.1	.187/4.749	.060/1.524	50 lb.	4.750	100	5,000
3M17-B	BLACK	17.0/434.1	.187/4.749	.060/1.524	50 lb.	4.750	100	5,000
EC20-N	NATURAL	19.50/495.0	.179/4.50	.055/1.41	50 lb.	5.900	100	1,000
EC20-B	BLACK	19.50/495.0	.179/4.50	.055/1.41	50 lb.	5.900	100	1,000
EC25-N	NATURAL	25.25/641.0	.190/4.85	.065/1.62	50 lb.	7.000	100	1,000
EC25-B	BLACK	25.25/641.0	.190/4.85	.065/1.62	50 lb.	7.000	100	1,000

Nylon Characteristics

Operating Characteristics of Nylon Tie Wraps

CABLE TIE MATERIAL	TEMPERATURE RATING	UL FLAME RATING	ENVIRONMENT
NYLON GENERAL PURPOSE	185°F 85°C	94V-2	INDOOR
BLACK NYLON UV STABILIZED	185°F 85°C	94V-2	INDOOR & OUTDOOR



*Minimum installation temperature is greater than 32°F or 0°C

Economy Tie Wraps are:

PRICE - Low cost.

FASTER - Low insertion and pull through force.

STRONGER - Tensile strength is achieved.

PURER - Manufactured from filtered nylon reducing particle contamination.

EASIER - Angled tail provides quicker initial insertion alignment and tail finger grips allow easier handling and tightening.

SAFER - Rounded edges provides added safety and eliminates insulation damage.

