




# Data Sheet

## 3M Specialty Terminals

TRV-R6 thru TRV-Y12  
 Ring Tongue, Vinyl Insulated, Butted Seam



Product Number	Wire Range (AWG)	Stud Size	W	C	L	E	Thickness	Barrel Length	Barrel I.D.	Maximum Insulation Diameter
TRV-R6	22-18	6	0.25	0.22	0.80	0.67	0.030	0.25	0.070	0.145
TRV-R8	22-18	8	0.33	0.29	0.90	0.74	0.030	0.25	0.070	0.145
TRV-R10	22-18	10	0.33	0.29	0.90	0.74	0.030	0.25	0.070	0.145
TRV-B6	16-14	6	0.25	0.22	0.80	0.67	0.030	0.25	0.090	0.170
TRV-B8	16-14	8	0.33	0.29	0.90	0.74	0.030	0.25	0.090	0.170
TRV-B10	16-14	10	0.33	0.29	0.90	0.74	0.030	0.25	0.090	0.170
TRV-B14	16-14	1/4	0.47	0.40	1.08	0.85	0.030	0.25	0.090	0.170
TRV-B56	16-14	5/16	0.56	0.40	1.13	0.85	0.030	0.25	0.090	0.170
TRV-B38	16-14	3/8	0.56	0.40	1.13	0.85	0.030	0.25	0.090	0.170
TRV-Y6	12-10	6	0.28	0.29	0.98	0.84	0.040	0.25	0.135	0.250
TRV-Y8	12-10	8	0.38	0.29	1.03	0.84	0.040	0.25	0.135	0.250
TRV-Y10	12-10	10	0.38	0.29	1.03	0.84	0.040	0.25	0.135	0.250
TRV-Y14	12-10	1/4	0.59	0.44	1.29	0.99	0.040	0.25	0.135	0.250
TRV-Y56	12-10	5/16	0.59	0.44	1.29	0.99	0.040	0.25	0.135	0.250
TRV-Y38	12-10	3/8	0.59	0.44	1.29	0.99	0.040	0.25	0.135	0.250
TRV-Y12	12-10	1/2	0.75	0.57	1.50	1.12	0.040	0.25	0.135	0.250

## Installation Information


### WARNING


Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style), or TR-490 (ratchet style) hand tools.



 Barrel Crimp (Electrical)

## Engineering Specification

Crimp-type terminals shall, electrically and mechanically, connect to a pre-stripped end of a stranded copper wire and have a flat tongue portion with a central opening for mounting around a screw or stud.

The terminal line shall offer tongue variations in hole (stud) size (6, 8 10, etc.) and configuration (ring, fork, block fork, flanged block fork, locking fork, etc.): and barrel variations in wire (AWG) size (22-18, 16-14, 12-10, etc.) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated with insulation grip, etc.). The terminal line shall have regulatory agency coverage (UL Listing, CSA Certification). The terminal tongue shall be marked with the wire range and manufacturer's symbol (↑).

The vinyl-insulated, butted seam ring tongue terminal shall be tin-plated, annealed copper, with the tongue having a specified stud hole (size 2 thru 1/2 in.) and a butted seam barrel covered by a molded vinyl funnel entry sleeve, color coded and sized for a specified (AWG) wire range (22-18, 16-14, 12-10).

Insulated terminals shall be UL Listed and CSA Certified for 600 Volts maximum building wire: 1000 Volts maximum in signs, fixtures and luminaries and have a maximum operating temperature of 221°F (105°C).

3M is a trademark of 3M.

is a trademark of Underwriters Laboratories.

is a trademark of Canadian Standards Association.

### IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

**Warranty; Limited Remedy; Limited Liability.** This product will be free from defects in material and manufacture as of the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**