

Specifications


| Model | TPC80 | TPC80H |
|------------------------------|---------------------------|---------------------------|
| Engine | Kohler CH270 | Honda GX160 |
| HP | 6 | 5.5 |
| kW | 4.5 | 4.1 |
| Compaction of Cohesive Soi | ls 10" | 10" |
| Compaction of Granular Soils | s 22" | 22" |
| Plate Size | 16.5" x 21.5" | 16.5" x 21.5" |
| Compaction Force | 3,000 lbs/ft ² | 3,000 lbs/ft ² |
| Vibration Frequency | 100 Hz | 100 Hz |
| Vibrations per Minute | 3,600 VPM | 3,600 VPM |
| Travel Speed | 79 ft/min | 79 ft/min |
| Water Tank Capacity | N/A | N/A |
| Operating Weight | 182 lbs | 182 lbs |
| Package Dimensions | 21" x 17" x 37" | 21" x 17" x 37" |

KOHLER. ENGINES



Kohler CH270 Engine 6HP / 208cc

Honda GX160 Engine 5.5HP / 163cc





Raised Edge Plate for No Dig Compaction

High Resistance NSK Bearings





3 Year Engine Warranty 1 Year Product Warranty

FEATURES

- Compaction force of 3000 lbs/ft² at 6,400 blows/min
- Compaction of cohesive and granular soils up to 22 in
- Travel speed of 79 ft/min
- Versatile 16.5" x 21.5" plate works around narrow spaces
- A full 2 dBA quieter than competitive models
- Front and rear lifting handles for greater portability
- Anti-vibratory handle for optimal user comfort