



Product Datasheet

New 2021 Edition 2>Downlights Fixed LED

10110TD/W/C



10W LED recessed downlight, IP54. Suitable for Indoor/Outdoor installation.

Complete with 250mA driver.

Complies with standard EN60598-1 and any other specific standards.













Downloads









Dimensions




Physical Specification

Item Group	New 2021 Edition 2
Family	Downlights Fixed LED
Order Code	10110TD/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	67mm
Diameter	115mm
Cutout Hole Diameter	95mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes

Outdoor	Yes
Adjustable	No
ectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	39V
Safety Class	<u> </u>
Power(Watts)	9W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7-9,2W
Power Factor	0,9
Constant Current	Yes
Output	250mA
Voltage Range	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	ONE
Illumination Data	
	4000K
Colour Temperature	4000K 850lm
Colour Temperature Lumen Output	850lm
Colour Temperature Lumen Output Light Efficiency	850lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	850lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	850lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	850lm 85lm/W 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	850lm 85lm/VV 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	850lm 85lm/W 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	850lm 85lm/W 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	850lm 85lm/W 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	850lm 85lm/W 80 60° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	850lm 85lm/W 80 60° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length Box Width	850lm 85lm/W 80 60° Yes 14cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length Box Width Box Height	850lm 85lm/W 80 60° Yes 14cm 14cm 8cm

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

