

Product Datasheet

www.1-light.eu

New 2023 Edition 2>Downlights Fixed LED

10120UV/B



20W SMD LED UGR19 downlight with adjustable CCT, IP44.


Complete with 550mA driver.

Complies with standard EN60598-1 and any other specific standards.





Dimensions



Gallery



Physical Specification

Item Group

New 2023 Edition 2

_	\sim	\sim	`'	\ /
_	а			v
	Q			y

Downlights Fixed LED

Order Code	10120UV/B
Colour	Black
Material	Die Cast
Shape	Circular
Height	55mm



Diameter	190mm
Cutout Hole Diameter	170mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes
Adjustable	No
IK Rating	4
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	

Input Type	Constant Current
Input Current	550mA

Voltage	36V
Safety Class	
Power(Watts)	19,8W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835



LED Brand

F Mark

Epistar

F

Gear	

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,75-22W
Power Factor	0,9
Constant Current	Yes
550mA	25-40V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload

Illumination Data

Colour Temperature	3000K-4000K-6000K
Lumen Output	1500lm
Light Efficiency	75lm/W
CRI	80

Illumination Diagram		
UGR	9	

Packing Info

Box Weight

0.615kg



Pcs/Carton	20
Barcode	5291889076414

Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to one light!



