



# **Product Datasheet**

## 06 Downlights Fixed LED>Architectural Downlights

10128/G/W



28W LED architectural downlight, IP20.

Complete with LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads





Dimensions



#### Gallery




#### Physical Specification

Product Type	Gear
Item Group	06 Downlights Fixed LED
Family	Architectural Downlights
Order Code	10128/G/W
Colour	Grey
Material	Die Cast
Diffuser Material	Acrylic

Shape	Circular
Height	85mm
Diameter	195mm
Cutout Hole Diameter	169mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
	D. 201
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
Dimmable	No F/
F Mark	F
Fitting	
	Comptant Current
Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Manufacturer	One Light
Illumination Data	
Colour Temperature	3000K
Lumen Output	1150lm
Light Efficiency	41Im/W
CRI	80
Beam Angle	90°
Illumination Diagram	
Packing Info	
Box Length	25cm
Box Width	21,5cm
Box Height	11,5cm
Pcs/Carton	10
Barcode	5291889027393
HS Code	9405409900
Energy Label	



### Certification & Warranty

Warranty	2 Years
Wee Directive	Yes



