

Product Datasheet

www.1-light.eu

04 Recessed Spots Adjustable LED>The COB Fire Rated

11106PF/C



6W LED Fire Rated Recessed adjustable spot, IP20.

Requires 350mA driver.

Complies with standard EN60598-1 and any other specific standards.

















Downloads









Dimensions

Dimensions are complete with the ring.







Gallery



Must be ordered separately



050044/B



050044/C



050044/MC



050044/W



89008

Physical Specification Item Group 04 Recessed Spots Adjustable LED Family The COB Fire Rated Order Code 11106PF/C Colour White Material Die Cast Circular Shape Height 70mm Diameter 89mm **Cutout Hole Diameter** 75mm **Recessed Ceiling** Yes Depth Required 90mm Indoor Yes Adjustable 1 Direction

Electrical Characteristics


Fitting	
Input Type	Constant Current
Input Current	350mA
Safety Class	<u> </u>
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	F

Colour Temperature Lumen Output 530Im Light Efficiency 88,33Im/W CRI Beam Angle 4000K 530Im 80 40°

Packing Info Box Length 12cm Box Width 11cm Box Height 8,5cm Box Weight 0,322Kg Pcs/Carton 20 Barcode 5291889047155 HS Code 9405409900

Energy Label

Illumination Data



Certification & Warranty

Warranty	3 Years
Weee Directive	Yes



