




Product Datasheet

04 Recessed Spots Adjustable LED>The Mirror Recessed Cylinders

11106T/W/W



6W Adjustable Dark light recessed spot, IP20.

Complete with 135mA driver.

Complies with standard EN60598-1 and any other specific standards.





Downloads










Dimensions



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The Mirror Recessed Cylinders
Order Code	11106T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	55mm
Diameter	59mm
Cutout Hole Diameter	52mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	135mA
Voltage	40V
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Osram
LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,4-5,67W
Power Factor	0,5
Constant Current	Yes
Output	135mA
Voltage Range	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C+50°C
Operating Temp	75°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection
Ilumination Data	
Ilumination Data Colour Temperature	3000K
	3000K 480lm
Colour Temperature	
Colour Temperature Lumen Output	480lm
Colour Temperature Lumen Output Light Efficiency	480lm 80lm/W
Colour Temperature Lumen Output Light Efficiency CRI	480lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	480lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	480lm 80lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	480lm 80lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	480lm 80lm/W 90 38° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton	480lm/W 90 38° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton Barcode	480lm 80lm/W 90 38° Yes 50 5291889075325
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton	480lm/W 90 38° Yes

Certification & Warranty

switch to one light!

