

Product Datasheet

11107B/W/C

New 2021 Edition 3>Recessed Spots Adjustable LED



7W recessed adjustable spot LED. Suitable for residential and commercial applications, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.





Gallery



Physical Specification

Item Group

New 2021 Edition 3

		••	
	\mathbf{n}		\ /
- a	m		v
			Y

Recessed Spots Adjustable LED

Order Code	11107B/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	55mm



Diameter	90mm
Cutout Hole Diameter	75mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	21V

Safety Class	
Power(Watts)	6,3W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Epistar



LED Number	
------------	--

F Mark

1

F

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,2-7,2W
Power Factor	0,5
Constant Current	Yes
300mA	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload


Illumination Data

Colour Temperature	4000K
Lumen Output	560lm
Light Efficiency	80lm/W
CRI	80

60°

Illumination Diagram






Box Length

12,5cm



Box Width	6cm
Box Height	11,5cm
Box Weight	0,225Kg
Pcs/Carton	50
Barcode	5291889070931
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to one light!



