




Product Datasheet

04 Recessed Spots Adjustable LED>The COB Dark Light Range

11107FD/B/W



7W COB LED Adjustable Dark Light recessed spot IP20.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions




Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Dark Light Range
Order Code	11107FD/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	83mm
Diameter	95mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	21V
Safety Class	
Power(Watts)	6,2W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Epistar
LED Number	1
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,2-7,2W
Power Factor	0,9
Constant Current	Yes
300mA	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Colour Temperature	3000K
Lumen Output	560lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	11,5cm
Box Width	10cm
Box Height	11,5cm
Box Weight	0,281Kg
Pcs/Carton	50
Barcode	5291889052371
HS Code	9405409900



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!

