

New 2023 Edition 2>Downlights Adjustable LED

11115G/B/W



15W COB LED zoomable 15°-45° adjustable downlight with removable honeycomb.

Supplied with 350mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification


Item Group	New 2023 Edition 2
Family	Downlights Adjustable LED
Order Code	11115G/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	47mm

Diameter	105mm
Cutout Hole Diameter	98mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	2 Directions


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	41V
Safety Class	
Power(Watts)	14,35W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

LED Number	1
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9,45-14,7W
Power Factor	0,92
Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KGP
Protection	Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1500lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	15°-45°
Illumination Diagram	

Packing Info

Pcs/Carton	27
Barcode	5291889076452

Warranty

5 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

