

New 2023 Edition 2>Downlights Adjustable LED

## 11128G/B/W



28W COB LED zoomable 15°-45° adjustable downlight with removable honeycomb.

Supplied with 750mA driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery






### Physical Specification


Item Group	New 2023 Edition 2
Family	Downlights Adjustable LED
Order Code	11128G/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	58mm

Diameter	134mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	2 Directions


## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	34,1V
Safety Class	
Power(Watts)	25,575W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

LED Number	1
<b>Gear</b>	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	20,25-30W
Power Factor	0,95
Constant Current	Yes
750mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KGP
Protection	Short Circuit Protection,Overload Protection,No-load Protection

### Illumination Data

Colour Temperature	3000K
Lumen Output	2800lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	15°-45°
Illumination Diagram	

### Packing Info

Pcs/Carton	18
Barcode	5291889076476

HS Code

9405413990

Certification & Warranty

Warranty

5 years

switch to  
**one light!**

one  
LIGHT

