



Product Datasheet

08 Downlights Adjustable LED>The COB Round Downlights

11150B/W/W



50W COB LED extractable fitting with great flexibility on movement. Ideal for shops.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads








Dimensions





Gallery



Physical Specification


Item Group	08 Downlights Adjustable LED
Family	The COB Round Downlights
Order Code	11150B/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	175mm

Diameter	134mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	250mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Titting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1200mA
Voltage	38V
Safety Class	
Power(Watts)	45,6W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ

LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-50,4W
Power Factor	0,9
Constant Current	Yes
1200mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	75°C
Housing Material	Plastic
Brand	Eaglerise
Protection	Short circuit protection
Illumination Data	
Colour Temperature	3000K
Lumen Output	3750lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	40°
Illumination Diagram	
Packing Info	
Box Weight	1,25kg
	.,3

Pcs/Carton	12
Barcode	5291889046714
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	3 Years
Weee Directive	Yes

switch to one light!

