

04 Recessed Spots Adjustable LED > Recessed COB Cylinders

11207C/B/W



2x7W COB LED recessed adjustable spot, for general lighting applications.

Requires 700mA constant current LED drivers.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89015A

Related items



89015AT

Physical Specification



Item Group

04 Recessed Spots Adjustable LED


Family	Recessed COB Cylinders
Order Code	11207C/B/W
Colour	Black
Material	Die Cast
Shape	Rectangular
Length	168mm
Width	90mm
Height	90mm
Cutout Hole Diameter	2x83mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	10V
Safety Class	
Power(Watts)	2x7W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Citizen
LED Number	1
Cable Length	40cm
F Mark	


Illumination Data

Colour Temperature	3000K
Lumen Output	2x520lm
Light Efficiency	74,3lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	

Packing Info

Box Length	17,5cm
Box Width	9,5cm
Box Height	10cm
Pcs/Carton	24
Barcode	5291889058403
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

