

Product Datasheet

www.1-light.eu

New 2023 Edition 2>Wall & Ceiling LED

12115G/B/W




15W COB LED zoomable 15°-45° adjustable ceiling light with removable honeycomb.

Supplied with 350mA driver.

Complies with standard EN60598-1 and any other specific standards.



Dimensions



Physical Specification

CE

Downloads

Item Group	New 2023 Edition 2
Family	Wall & Ceiling LED
Order Code	12115G/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	95mm

Diameter	80mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	2 Directions



Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	41V
Safety Class	
Power(Watts)	14,35W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
LED Number	1

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes



Power(Watts)	10,5-14,7W
Power Factor	0,9
Constant Current	Yes
350mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KGP
Protection	Short Circuit Protection, Overload Protection, No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1500lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	15°-45°
Illumination Diagram	

Packing Info

Pcs/Carton	40
Barcode	5291889076377
HS Code	9405413990

Certification & Warranty



Warranty

5 years

switch to one light!



