

21 Industrial & Floodlights>The IP66 Industrial LED Range

38150LB/C



50W industrial linear light, IP66.

Complete with non-dimmable LED driver.

Supplied with 3 fixing clips.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery





Physical Specification

Item Group	21 Industrial & Floodlights
Family	The IP66 Industrial LED Range
Order Code	38150LB/C
Material	PC
Shape	Rectangular
Length	1510mm
Width	62mm


Height	58mm
Surface Ceiling	Yes
Surface Wall	Yes
Outdoor	Yes
IK Rating	8

Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP66
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	300mA
Power(Watts)	50W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	50W
Power Factor	0,9
Constant Current	Yes
300mA	116-167V
IP Rating	IP20
Safety Class	
Dimmable	No

Illumination Data

Colour Temperature	4000K
Lumen Output	5750lm
Light Efficiency	115lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	1.144kg
Pcs/Carton	9
Barcode	5291889074427
HS Code	9405114090

Energy Label



Energy Class

E

Energy Consumption

50KWh/1000h

Certification & Warranty

Warranty

2 years

switch to
one light!

one
LIGHT

