

New 2023 Edition 2>Office & Kitchen

## 38152R/B/W



40W Recessed linear with diffuser, ideal for offices.

Complete with 1000mA driver, 6pcs fixing clips, 4pcs connectors & 2pcs end cups.

Can be connected in line.

Complies with standard EN60598-1 and any other specific standards.




### Downloads



### Dimensions



### Gallery



### Physical Specification

Item Group

New 2023 Edition 2

Family

Office & Kitchen

Order Code

38152R/B/W

Colour

Black

Material

Aluminium

Diffuser Material



Plastic

Shape

Rectangular

Length	1210mm
Width	70mm
Height	60mm
Cutout Hole Width	60mm
Cutout Hole Length	1200mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No


### Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	


Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	36V
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	288

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W
Power Factor	0,95
Constant Current	Yes
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Metal
Output Terminal	Connector
Brand	BOKE

## Illumination Data

Colour Temperature	3000K
Lumen Output	3600lm
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

## Packing Info

Box Weight	2.325kg
Pcs/Carton	12

Barcode

5291889075615

HS Code

9405413990

Certification & Warranty

Warranty

3 years

switch to  
**one light!**

one  
LIGHT

