


New 2020 Edition 2>Office & Kitchen

38152RL/W/C



10W ceiling to wall corner for 38152R.

Complete with 200mA driver , 4pcs fixing clips, 4pcs connectors & 2pcs end cups.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

New 2020 Edition 2

Family

Office & Kitchen

Order Code

38152RL/W/C

Colour

White

Material

Aluminium

Diffuser Material



Plastic

Shape

Rectangular

Length	164x164mm
Width	70mm
Height	60mm
Cutout Hole Width	100x100mm
Cutout Hole Length	60mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No


Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	


Fitting	
Input Type	Constant Current
Input Current	200mA
Voltage	42V
Power(Watts)	8,4W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	72

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-8,4W
Power Factor	0,9
Constant Current	Yes
200mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Metal
Output Terminal	Connector
Brand	ATG


Illumination Data

Colour Temperature	4000K
Lumen Output	900m
Light Efficiency	90lm/W
CRI	80
Illumination Diagram	

Packing Info

Pcs/Carton	6
Barcode	5291889062684

Energy Label



Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

